

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

API No. 30-025-26571

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CLEAN OR PLUG BACK TO A DIFFERENT RESERVOIR.
(SEE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒	GAS WELL ☐	OTHER ☐	5a. Indicate Type of Lease State ☒ Fee ☐
Name of Operator Phillips Petroleum Company			5. State Oil & Gas Lease No. B-1585
Address of Operator Room 401, 4001 Penbrook Street, Odessa, Texas 79762			7. Unit Agreement Name East Vacuum Gb/SA Unit
Location of Well UNIT LETTER M 1310 FEET FROM THE West LINE AND 1310 FEET FROM THE South LINE, SECTION 22 TOWNSHIP 17-S RANGE 35-E NMPM.			8. Farm or Lease Name Gb/SA Unit, Tract 2230
15. Elevation (Show whether DF, RT, GR, etc.) 3947.0 GR			9. Well No. 003
			10. Field and Pool, or Wildcat Vacuum Gb/SA
			12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOBS ☒	
OTHER ☒ Total depth	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-14-79--MI Marc Drlg. Spud in w/11" bit. Drill to 355'--Run 9 jts. 8-5/8" 24#, K-55, ST&C csg. Howco cmt w/350 sxs Class "H" w/2% CaCl, 1/4#/sx Flocele. Circ 60 sxs cmt to surface. WOC 18 hrs.
12-15-79 - NU BOP - Test BOP & csg. 600 psi
12-25-79--Unable to run logs--Reached TD 4800'.

12-26-79--Ran 112 jts (4806.30') 4-1/2" 11.6# N80 ST&C csg to 4801'. Howco circ 10 bbl H₂O ahead. Cmt w/1200 sxs TLW. W/12# sx salt, 10% Diacel D, 1/4# Flocele 3#/sx Gilsonite. Tail in w/350 sxs Class "H" w/8# sx salt + 2% CaCl--Displ w/20 bbl acid + 85 bbl H₂O. Bumped plug w/1700#--plug held. Circ 130 sxs TLW to surface.

12-27-79--WOC 18 hrs. Cut off head. Released rig 2 AM 12-27-79. Prep to complete.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed W. J. Mueller TITLE Senior Engineering Specialist DATE 12-27-79
Orig. Signed by Jerry Sexton
APPROVED BY Dist. 1. Supr. TITLE _____ DATE DEC 28 1979
CONDITIONS OF APPROVAL, IF ANY _____