

NO. OF COPIES RECEIVED		
DISTRIBUTION		
ANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

API No. 30-025-26572

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT -- (FORM C-101) FOR SUCH PROPOSALS.)

OIL
WELL ☒

GAS
WELL ☐

OTHER ☐

Name of Operator

Phillips Petroleum Company

Address of Operator

Room 401, 4001 Penbrook Street, Odessa, Texas 79762

Location of Well

UNIT LETTER 0 1330 FEET FROM THE East LINE AND 10 FEET FROM

THE South LINE, SECTION 22 TOWNSHIP 17-S RANGE 35-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3935.4 GR

3a. Indicate Type of Lease

State ☒

Fee ☐

5. State Oil & Gas Lease No.

B-2735

7. Unit Agreement Name

East Vacuum Gb/SA Unit

8. Farm or Lease Name East Vacuum

Gb/SA Unit, Tract 2271

9. Well No.

003

10. Field and Pool, or Wildcat

Vacuum Gb/SA

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOBS ☒
OTHER Total depth ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-14-79--MI Marc Drlg. Spud in w/11" bit. Drill to 351'--Run 9 jts 8-5/8", 24#, K55 8 Rd ST&C csg. Howco cmt w/350 sxs Class "H" w/2% CaCl 1/4#sx Flocele. Circ 80 sxs cmt to surface. WOC 30 hrs.

12-15-79 - NU BOP - Test BOP and casing 600 psi

12-25-79--Ran Sonic, DL, Micro L & Gamma Ray--GIH

12-25-79--Reached TD 4800'. Run 5-1/2", 14#, K-55, STL ⑧ csg, 112 jts set @ 4800' Circ B/U--10 bbls H₂O ahead. Cmt w/1200 sxs TLW w/12# salt, 10% Diacel D. 1/4#sx Flocele, 3#7sx Gilsonite--Tail in w/350 sx Class "H" w/8# sx salt and 2% CaCl--Displ w/20 bbl acid + 94 bbls H₂O--Bump Plug--w/1800# Plug held--WOC 19 hrs. Circ 200 sxs TLW to surface. Rig released 5 AM, 12-26-79. Prep to complete.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

W. J. Mueller

TITLE Senior Engineering Specialist DATE 12-27-79

Orig. Signed by

Jerry Sexton
Dist. 1, Sup

APPROVED BY

TITLE

DATE

DEC 31 1979

CONDITIONS OF APPROVAL, IF ANY