

NO. OF COPIES RECEIVED		
DISTRIBUTION		
DATE		
FILE		
NO. OF COPIES		
AND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

API No. 30-025-26575

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT - "A" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Phillips Petroleum Company

Address of Operator

Room 401, 4001 Penbrook Street, Odessa, Texas 79762

Location of Well

UNIT LETTER G 1330 FEET FROM THE East LINE AND 1330 FEET FROM
THE North LINE, SECTION 28 TOWNSHIP 17-S RANGE 35-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3943.0 GR

3a. Indicate Type of Lease

State ☒

Fee ☐

5. State Oil & Gas Lease No.

B-1423

7. Unit Agreement Name

East Vacuum GB/SA Unit

8. Farm or Lease Name East Vacuum GB/SA Unit, Tract 2819

9. Well No.

004

10. Field and Pool, or Wildcat

Vacuum GB/SA

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☒

CASING TEST AND CEMENT JOB ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

Total depth

☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

01-03-80--MI Cactus Drlg spud in w/12-1/4" bit. Ran 351' 8-5/8" 24# K-55, ST&C csg set at 350'. Cmt w/350 sxs Cl "H" w/2% CaCl and 1/4# Flocele--circ 80 sxs to surface--temp of cmt 65°, zone temp 63°, estimate of cmt strength 2250#, and cmt in place 12 hrs prior to starting test.

01-04-80--NU BOP's. Test Blind rams and csg to 600#. Drld float and cmt and 20' drld ahead w/7-7/8" hole.

01-13-80--Reached TD 4800'. Logging.

01-15-80--Ran 119 jts of 5-1/2 17# N-80 csg set at 4799'. Cmt w/1345 sxs TLW, w/12# salt, 10% DD, 1/4# Flocele, 400 sxs Cl "H", 5# salt. Circ 675 to surface. Released rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

W. J. Mueller

TITLE Sr. Engineering Specialist

DATE January 21, 1980

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: