

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-101
Revised 10-1-78

5A. Indicate Type of Lease

STATE ☒ FEE ☐

5. State Oil & Gas Lease No.

7. Unit Agreement Name

6. Farm or Lease Name

New Mexico State

9. Well No.

2

10. Field and Pool, or Wildcat

Scharb

12. County

Lea

19. Proposed Depth

11,000

19A. Formation

Bone Spring

20. Rotary or C.T.

Rotary

21. Elevations (Show whether DE, RT, etc.)

3949.5 GR

21A. Kind & Status Plug Bond

One Well (Applied For)

21B. Drilling Contractor

Cactus

22. Approx. Date Work will start

2-15-80

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17-1/2	13-3/8	54.50	500	450	Surface
12-1/4	8-5/8	24 & 32	4200	400	3200
7-7/8	4-1/2	11.6	11,000	500	9000

1. Drill 17-1/2" hole to approx. 500', set 13-3/8" csg, cement w/450 sx "C" to Surface.
2. Inst. BOP (5000# WP.) drill 12-1/4" hole to approx. 4200', set 8-5/8" csg, cmt w/400 sx "C" est. top cmt @ 3200'.
3. Drill 7-7/8" hole to approx 11,000'. DST & Log well. Run 4-1/2" csg, cmt w/500 sx "H" calc. Top of cmt 9000'.

****Cement on the intermediate casing must be brought from the top of the salt or anhydrite to the surface casing. This can be done by either circulating the intermediate casing with cement, or a DV tool at the top of the salt.**

R-6261 N SL

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed J. R. Colter Title Engineer Date December 10, 1979

(This space for State Use)

APPROVED BY [Signature] TITLE SUPERVISOR DATE FEB 10 1980

CONDITIONS OF APPROVAL, IF ANY:

**See Above