

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

API No. 30-025-26649

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
B-1576-3	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. SEE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

6. Indicate Type of Well OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. Unit Agreement Name East Vacuum Gb/SA Unit
8. Name of Operator Phillips Petroleum Company		8. Former or Lease Name East Vacuum Gb/SA Unit, Tract 3229
9. Address of Operator Room 401, 4001 Penbrook St., Odessa, Texas 79762		9. Well No. 007
10. Location of Well UNIT LETTER <u>K</u> <u>2600</u> FEET FROM THE <u>South</u> LINE AND <u>2500</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>17-S</u> RANGE <u>35-E</u> HMPM.		10. Field and Pool, or Wildcat Vacuum Gb/SA
11. Elevation (Show whether DF, RT, GR, etc.) 3962.4 GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	
		OTHER <u>total depth</u> ☒	

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 2-13-80 MI Cactus Drlg. Spud w/12-1/4" bit. Ran one jt 9-5/8", 40#, K-55, STC csg set at 365'. Cmt w/400 sxs Cl "H" w/2% CaCl and 1/4#/sx Flocele. Circ 75 sxs to surface. Temp cmt 60°, zone temp 63°, strength of cmt 2200 PSE, cmt in place 12-1/2 hrs before testing. Test BOP's and csg OK.
- 2-27-80 Reached 4800' TD. Ran 115 jts, 7", 23#, K-55, STC csg set at 4800'. Cmt w/1200 sxs TLW w/10% DD and 12#/sx salt and 1/4#/sx Flocele and 3#/sx Gilsonite. Tailed in w/400 sxs Class "H" w/5#/sx CaCl. Circ 500 sxs to surface.
- 2-29-80 Released rig--prep to perf.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

W. J. Mueller TITLE Senior Engineering Spec. DATE 3-20-80
Orig. Signed By
Jerry Sexton
Dist 1, Supy.
APPROVED BY TITLE DATE
CONDITIONS OF APPROVAL, IF ANY: