

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.

30-025-26735

Indicate Type of Lease

STATE ☐

FEE ☒

State Oil & Gas Lease No.

Lease Name or Unit Agreement Name

MESCALERO RIDGE

Well No.

1

Pool name or Wildcat

SCHARB (BONE SPRING)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

Name of Operator

SOUTHWEST ROYALTIES, INC.

Address of Operator

P. O. BOX 11390; MIDLAND, TX 79702

Well Location

Unit Letter K : 1980 Feet From The SOUTH Line and 1980 Feet From The WEST Line

17 Section

19S Township

35E Range

NMPM

LEA County

Elevation (Show whether DF, RKB, RT, GR, etc.)

3838' GL

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ANBANDONMENT ☐


CASING TEST AND CEMENT JOB ☐

OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) RU SERVICE CO. POH & LD PROD. EQUIPMENT.
- 2) RU WL. GIH & SET CIBP @ 9790'. CAP W/ 35 SX CMT. RD WS AND WL. -TAG
- 3) MIRU PLUGGING CONTRACTOR. LOAD W/ MUD. CUT 5 1/2" CSG @ +/- 6000'. POOH & LD 5 1/2" CSG/
- 4) SPOT 45 SX CMT PLUG FROM +/- 5925' TO 6075' (across csg stub). -TAG
- 5) SPOT 50 SX CMT PLUG FROM 5065' to 5215' (across 9 5/8" shoe). -TAG
- 6) SPOT 50 SX CMT PLUG FROM 3000' - 3150'.
- 7) SPOT 50 SX CMT PLUG FROM 1950' - 2100'.
- 8) SPOT 50 SX CMT PLUG FROM 545' - 695'. -TAG
- 9) SPOT 35 SX CMT PLUG FROM 3' - 103'.
- 10) CUT OFF CSG WELD ON PLATE. INSTALL P&A MARKER. RESTORE SURFACE LOCATION

THE COMMISSION MUST BE NOTIFIED 24
HOURS PRIOR TO THE BEGINNING OF
PLUGGING OPERATIONS FOR THE C-103
TO BE APPROVED.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Bill R. Keathly

TITLE AGENT

DATE 11-13-01

TYPE OR PRINT NAME Bill R. Keathly

TELEPHONE NO. 915 686-9927

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

S
L

Q

APC #

30-025-26735

WT K

545'-695'

1950 - 2100'

3000 - 3150'

7/28/83 Re-entry

9/30/83 Re-entry

5065'-5215' completed

IP'd 26180, 226mcf, 158'

7880'

7880' (csg) leaks 5920d
w/ 30054 & 85/89

Mud

5-1/2" csg (as ran)

FS

2 jts, 20#, N-80 LTC

FC

1 jt, 20#, N-80 LTC

10 jts, 17#, L-80 LTC

20 jts, 17#, N-80 LTC

36 jts, 17#, K-55 LTC

180 jts, 15.5#, K-55 LTC

emented w/215 sxs cl "H"

TD @ 10,229'

PETD10,150'

Bone Spring Perfs: 9882'-9903' w/2 jspt

TOC Calc @ 9483'
Calc @ 9755'
CIRP Calc @ 9790'

ED
FACTS
000