	CUTT IU MA NA MA			
rm 9-331	UNITED STATES	SUBMIT IN TRIPLICAT :* OD (Other Instructions )	Form approve Budget Burea	d. u No. 42 -R1424.
uy 1963) DEP.	ARTMENT THE INTERIO	OR verse side?	5. LEASE DESIGNATION .	
	GEOLOGICAL SURVEY		NM-6870	
CUNIDAY	NOTICES AND REPORTS C	N WELLS	6. IF ISHIAN, ALLOTTEE	OR TRIBE NAME
the second state of the fail	r proposals to drill or to deepen or plug by	nck to a different reservoir.		
Use "A	PPLICATION FOR PERMIT- for such pr	oposals.)		
			T. UNIT AUREEMENT NA.	ME
OIL GAS X OTHER		S. FAEM OR LEASE NAME		
NAME OF OPERATOR		Pipeline Deep Unit Fede		
Union Oil Company	f of California		9. WELL NO.	<u>o Unil rede</u>
ADUBERS OF OPERATOR	Midland Tawar 70702		5	
P. O. Box b/1	- Midland, Texas 79702 Section clearly and in accordance with any	State requirements.*	10. FIELD AND POOL, QI	WILDCAT
See also space 17 below.) At surface			Undesignated (N. Quail Ri	dge Morrow
1980' FSL	and 660' FWL		11. SEC., T., R., M., OR B SURVET OR AREA	LE. AND
1,00 102 1				· · · · ·
			Sec. 7, T-19	
PERMIT NO.	15. ELEVATIONS (Show whether DF	, RT, GR, etc.)	12. COUNTY OR PARISH	
	3743' GR.		Lea	New Mexico
s. Ch	eck Appropriate Box To Indicate N	lature of Notice, Report, or (	Other Data	
	OF INTENTION TO:		UENT REPORT OF :	
NOTICE				
TEST WATER SHUT-OFF	- PULL OR ALTER CASING	WATER SHUT-OFF	ALTERING C	
FRACTURE TREAT	- MULTIPLE COMPLETE	PRACTURE TREATMENT	ABANDONME	
SHOOT OF ACIDIZE	- ABANDON*	(Other) Set interm		X
REPAIR WELL	CHANGE PLANS	(Norr Report result	s of multiple completion pletion Report and Log fo	
		Completion or Recom	detion Report and Log fo	
4-14-80 - W.O.C. Ran 12 4-25-80 - Ran 12	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8"	D.P. and tested B.O.P 503' to 5,300'. OD 43.5# (4,567.15'	<ul> <li>to 700 psi, h</li> <li>S-95 and 40#</li> </ul>	te of starting any s and somes perti- neld OK. (705.21')
<ul> <li>7. DESCRIBE PROPOSED OR CONFINENCE of Contract proposed work. If well in nent to this work.)*</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12</li> <li>K-55 n with 8</li> <li>4-26-8</li> <li>cement</li> </ul>	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.	<ul> <li>it details, and give pertinent datestions and measured and true verifieds</li> <li>0.P. and tested B.O.P.</li> <li>i OD 43.5# (4,567.15')</li> <li>D.V. Tool set at 1,7</li> <li>i Cl. "C" cement, comestication of the set of</li></ul>	<ul> <li>including estimated data call depths for all marker</li> <li>to 700 psi, h</li> <li>S-95 and 40#</li> <li>91'. First stapleted at 2:00</li> <li>Lite Wate and</li> </ul>	te of starting any s and somes perti- neld OK. (705.21') ge cemented A.M. Cl. "C"
7. DESCRIBE PHOPOSED OR COMPL proposed work. If well i hent to this work.)* 4-14-80 - W.O.C. Ran 12 4-25-80 - Ran 12 K-55 n with 8 4-26-8	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.	<ul> <li>it details, and give pertinent datestions and measured and true verifieds</li> <li>0.P. and tested B.O.P.</li> <li>i OD 43.5# (4,567.15')</li> <li>D.V. Tool set at 1,7</li> <li>i Cl. "C" cement, comestication of the set of</li></ul>	<ul> <li>including estimated data call depths for all marker</li> <li>to 700 psi, h</li> <li>S-95 and 40#</li> <li>91'. First stapleted at 2:00</li> <li>Lite Wate and</li> </ul>	te of starting any s and somes perti- neld OK. (705.21') ge cemented A.M. Cl. "C"
<ul> <li>7. DESCRIBE PROPOSED OR CONFINENCE of Contract work. If well in the tothis work.)*</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12</li> <li>K-55 n with 8</li> <li>4-26-8</li> <li>cement</li> </ul>	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.	<ul> <li>and tested B.O.P.</li> <li>and tested B.O.P.</li> <li>b) P. and tested B.O.P.</li> <li>b) OD 43.5# (4,567.15')</li> <li>c) D.V. Tool set at 1,7</li> <li>c) Cl. "C" cement, com</li> <li>d) with 1,100 sx HOWCO</li> <li>8-26-80, cement circ</li> </ul>	<ul> <li>including estimated data call depths for all marker</li> <li>to 700 psi, h</li> <li>S-95 and 40#</li> <li>91'. First stapleted at 2:00</li> <li>Lite Wate and ulated to surfa</li> </ul>	te of starting any s and somes perti- neld OK. (705.21') ge cemented A.M. Cl. "C" ace.
<ul> <li>7. DESCRIBE PhotoSED OR COMPL proposed work. If well i nent to this work.)*</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12 K-55 n with 8 4-26-8 cement</li> </ul>	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.	<ul> <li>and tested B.O.P.</li> <li>and tested B.O.P.</li> <li>b) P. and tested B.O.P.</li> <li>b) OD 43.5# (4,567.15')</li> <li>c) D.V. Tool set at 1,7</li> <li>c) Cl. "C" cement, com</li> <li>d) with 1,100 sx HOWCO</li> <li>8-26-80, cement circ</li> </ul>	<ul> <li>including estimated data call depths for all marker</li> <li>to 700 psi, h</li> <li>S-95 and 40#</li> <li>91'. First stapleted at 2:00</li> <li>Lite Wate and ulated to surfa</li> </ul>	te of starting any s and somes perti- neld OK. (705.21') ge cemented A.M. Cl. "C" ace.
<ul> <li>7. DESCRIBE Phonosed on conference of the second work. If well in the this work. If well in the this work.</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12</li> <li>K-55 n with 8</li> <li>4-26-8</li> <li>cement</li> </ul>	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.	<ul> <li>and tested B.O.P.</li> <li>and tested B.O.P.</li> <li>b) P. and tested B.O.P.</li> <li>b) OD 43.5# (4,567.15')</li> <li>c) D.V. Tool set at 1,7</li> <li>c) Cl. "C" cement, com</li> <li>d) with 1,100 sx HOWCO</li> <li>8-26-80, cement circ</li> </ul>	<ul> <li>including estimated data call depths for all marker</li> <li>to 700 psi, h</li> <li>S-95 and 40#</li> <li>91'. First stapleted at 2:00</li> <li>Lite Wate and ulated to surfa</li> </ul>	te of starting any s and somes perti- neld OK. (705.21') ge cemented A.M. Cl. "C" ace.
7. DESCRIBE PHOPOSED OR COMPL proposed work. If well i nent to this work.)* 4-14-80 - W.O.C. Ran 12 4-25-80 - Ran 12 K-55 n with 8 4-26-8 cement	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.	<ul> <li>and tested B.O.P.</li> <li>and tested B.O.P.</li> <li>b) P. and tested B.O.P.</li> <li>b) OD 43.5# (4,567.15')</li> <li>c) D.V. Tool set at 1,7</li> <li>c) Cl. "C" cement, com</li> <li>d) with 1,100 sx HOWCO</li> <li>8-26-80, cement circ</li> </ul>	c. including estimated dat cal depths for all marker . to 700 psi, h ) S-95 and 40# 91'. First stapleted at 2:00 Lite Wate and ulated to surfa	te of starting any s and somes perti- neld OK. (705.21') ge cemented A.M. Cl. "C" ace.
<ul> <li>7. DESCRIBE PROPOSED OR CONFINENCE of Contract proposed work. If well in nent to this work.)*</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12</li> <li>K-55 n with 8</li> <li>4-26-8</li> <li>cement</li> </ul>	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.	it details, and give pertinent date tions and measured and true verifi- 0.P. and tested B.O.P 503' to 5,300'. ' OD 43.5# (4,567.15' D.V. Tool set at 1,7 I Cl. "C" cement, com i with 1,100 sx HOWCO 8-26-80, cement circ	A including estimated dat cal depths for all marker ) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa	te of starting any s and somes perti- neld OK. (705.21') ge cemented A.M. Cl. "C" ace.
<ul> <li>7. DESCRIBE PhotoSED OR COMPL proposed work. If well i nent to this work.)*</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12 K-55 n with 8 4-26-8 cement</li> </ul>	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.	and tested B.O.P. (0) P. and tested B.O.P (0) Y. and tested B.O.P (0) 43.5# (4,567.15') D.V. Tool set at 1,7 (1) Cl. "C" cement, com (2) with 1,100 sx HOWCO (8-26-80, cement circ)	A including estimated dat cal depths for all marker ) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa	te of starting any s and somes perti- leld OK. (705.21') ge cemente A.M. Cl. "C" ice.
<ul> <li>7. DESCRIBE Phonosed on conference of the second work. If well in the this work. If well in the this work.</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12</li> <li>K-55 n with 8</li> <li>4-26-8</li> <li>cement</li> </ul>	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.	and tested B.O.P. (0) P. and tested B.O.P (0) Y. and tested B.O.P (0) 43.5# (4,567.15') D.V. Tool set at 1,7 (1) Cl. "C" cement, com (2) with 1,100 sx HOWCO (8-26-80, cement circ)	A including estimated dat cal depths for all marker ) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa	te of starting any s and somes perti- leld OK. (705.21') ge cemented A.M. Cl. "C" ace.
<ul> <li>7. DESCRIBE PhotoSED OR COMPL proposed work. If well i nent to this work.)*</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12 K-55 n with 8 4-26-8 cement</li> </ul>	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.	and tested B.O.P. (0) P. and tested B.O.P (0) Y. and tested B.O.P (0) 43.5# (4,567.15') D.V. Tool set at 1,7 (1) Cl. "C" cement, com (2) with 1,100 sx HOWCO (8-26-80, cement circ)	A including estimated dat cal depths for all marker ) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa	te of starting any s and somes perti- leld OK. (705.21') ge cemented A.M. Cl. "C" ace.
<ul> <li>7. DESCRIBE PhotoSED OR COMPL proposed work. If well i nent to this work.)*</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12 K-55 n with 8 4-26-8 cement</li> </ul>	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.	and tested B.O.P. (0) P. and tested B.O.P (0) Y. and tested B.O.P (0) 43.5# (4,567.15') D.V. Tool set at 1,7 (1) Cl. "C" cement, com (2) with 1,100 sx HOWCO (8-26-80, cement circ)	A including estimated dat cal depths for all marker ) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa	te of starting any s and somes perti- leld OK. (705.21') ge cemente A.M. Cl. "C" ice.
7. DESCRIBE PhotoSED OR COMPL proposed work. If well i nent to this work.)* 4-14-80 - W.O.C. Ran 12 4-25-80 - Ran 12 K-55 n with 8 4-26-8 cement W.O.C.	18 hours. Installed B.C 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 2, completed at 8:45 A.M.	and tested B.O.P. (0) P. and tested B.O.P (0) Y. and tested B.O.P (0) 43.5# (4,567.15') D.V. Tool set at 1,7 (1) Cl. "C" cement, com (2) with 1,100 sx HOWCO (8-26-80, cement circ)	A including estimated dat cal depths for all marker ) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa	te of starting any s and somes perti- leld OK. (705.21') ge cemente A.M. Cl. "C" ice.
7. DESCRIBE Photosed or Compu- proposed work. If well i nent to this work.)* 4-14-80 - W.O.C. Ran 12 4-25-80 - Ran 12 K-55 n with 8 4-26-8 cement W.O.C.	18 hours. Installed B.C. 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 30. Second stage cemented 31. completed at 8:45 A.M.	<pre>it details, and give pertinent date thens and measured and true verify 0.P. and tested B.O.P 503' to 5,300'. ' OD 43.5# (4,567.15' D.V. Tool set at 1,7 I Cl. "C" cement, com I with 1,100 sx HOWCO 8-26-80, cement circ</pre>	A including estimated dat cal depths for all marker ) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa MAY 19 1980 S. GEOLOGICAL SUF 1083S, NEW MEXIC	<pre>te of starting any s and somes perti- leld OK. (705.21') ge cementer A.M. Cl. "C" ice.</pre>
7. DESCRIBE PhotoSED OR COMPL proposed work. If well i nent to this work.)* 4-14-80 - W.O.C. Ran 12 4-25-80 - Ran 12 K-55 n with 8 4-26-8 cement W.O.C. 18. 1 hereby certify that the for SIGNED	<pre>18 hours. Installed B.C 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.</pre>	and tested B.O.P. (0) P. and tested B.O.P (0) Y. and tested B.O.P (0) 43.5# (4,567.15') D.V. Tool set at 1,7 (1) Cl. "C" cement, com (2) with 1,100 sx HOWCO (8-26-80, cement circ)	A including estimated dat cal depths for all marker . to 700 psi, h ) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa MAY 14 1980 S. GEOLOGICAL SUF HOBBS, NEW MEXIC	te of starting any s and somes perti- neld OK. (705.21') ge cemente A.M. Cl. "C" nce. VEY CO
<ul> <li>7. DESCRIBE PROPOSED OR COMPL proposed work. If well i nent to this work.)*</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12 K-55 n with 8 4-26-8 cement W.O.C.</li> </ul>	<pre>18 hours. Installed B.C 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.</pre>	<pre>it details, and give pertinent date thens and measured and true verify 0.P. and tested B.O.P 503' to 5,300'. ' OD 43.5# (4,567.15' D.V. Tool set at 1,7 I Cl. "C" cement, com I with 1,100 sx HOWCO 8-26-80, cement circ</pre>	A including estimated dat cal depths for all marker ) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa MAY 19 1980 S. GEOLOGICAL SUF 1083S, NEW MEXIC	te of starting any s and somes perti- neld OK. (705.21') ge cemente A.M. Cl. "C" nce. VEY CO
<ul> <li>7. DESCRIBE PROPOSED OR COMPL proposed work. If well in nent to this work.)*</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12 K-55 m with 8 4-26-8 cement W.O.C.</li> <li>18. 1 breeby certify that the for SIGNED Manual (This space for Federal or APPROVED BY</li> </ul>	<pre>18 hours. Installed B.C 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.</pre>	<pre>it details, and give pertinent date thens and measured and true verify 0.P. and tested B.O.P 503' to 5,300'. ' OD 43.5# (4,567.15' D.V. Tool set at 1,7 I Cl. "C" cement, com I with 1,100 sx HOWCO 8-26-80, cement circ</pre>	A including estimated dat cal depths for all marker . to 700 psi, h ) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa MAY 14 1980 S. GEOLOGICAL SUF HOBBS, NEW MEXIC	te of starting any s and somes perti- neld OK. (705.21') ge cementer A.M. Cl. "C" ace. VEY CO
<ul> <li>7. DESCRIBE PROPOSED OR COMPL proposed work. If well i nent to this work.)*</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12 K-55 n with 8 4-26-8 cement W.O.C.</li> <li>18. 1 bereby cerffs that the for SIGNED Additional complexity of the second seco</li></ul>	<pre>18 hours. Installed B.C 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.</pre>	<pre>it details, and give pertinent date thens and measured and true verify 0.P. and tested B.O.P 503' to 5,300'. ' OD 43.5# (4,567.15' D.V. Tool set at 1,7 I Cl. "C" cement, com I with 1,100 sx HOWCO 8-26-80, cement circ</pre>	A including estimated dat including estimated dat including for all marker . to 700 psi, h ) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa MAY 19 1980 S. GEOLOGICAL SUF HOBBS, NEW MEXIC DATE May ACCEPTED FC DATE	te of starting any s and somes perti- neld OK. (705.21') ge cemented A.M. Cl. "C" ice. NVEY CO 14, 1980 RRECORD
<ul> <li>7. DESCRIBE PROPOSED OR COMPL proposed work. If well i nent to this work.)*</li> <li>4-14-80 - W.O.C. Ran 12</li> <li>4-25-80 - Ran 12 K-55 n with 8 4-26-8 cement W.O.C.</li> <li>18. 1 bereby certify that the for SIGNED A second se</li></ul>	<pre>18 hours. Installed B.C 2-1/4" bit, drilled from 5 28 jts. (5,272') of 9-5/8" new casing set at 5,295', 300 sx HOWCO Lite Wate and 30. Second stage cemented 5, completed at 8:45 A.M.</pre>	<pre>it details, and give pertinent date thens and measured and true verify 0.P. and tested B.O.P 503' to 5,300'. ' OD 43.5# (4,567.15' D.V. Tool set at 1,7 I Cl. "C" cement, com I with 1,100 sx HOWCO 8-26-80, cement circ</pre>	A including estimated dat (a) depths for all marker (b) S-95 and 40# 91'. First sta pleted at 2:00 Lite Wate and ulated to surfa MAY 14 1980 S. OEOLOGICAL SUF 1083S, NEW MEXIC (DATE May ACCEPTED FO	te of starting any s and somes perti- neld OK. (705.21') ge cemented A.M. Cl. "C" ice. NVEY CO 14, 1980 RRECORD