

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 63373	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation		8. Farm or Lease Name Lea "ED" State (NCT-A)
3. Address of Operator P. O. Box 670, Hobbs, NM 88240		9. Well No. 4
4. Location of Well UNIT LETTER <u>K</u> <u>2230</u> FEET FROM THE <u>South</u> LINE AND <u>2200</u> FEET FROM THE <u>West</u> LINE, SECTION <u>16</u> TOWNSHIP <u>19S</u> RANGE <u>34E</u> N.M.P.M.		10. Field and Pool, or Wildcat Quail Ridge-Bone Springs
15. Elevation (Show whether DF, RT, GR, etc.) 3774' GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11" hole 8-4-80. RU & ran 81 joints & 1 cut joint 8-5/8" 32# & 24# K-55 LT&C & ST&C (351' 32#) (2748' 24#) (3199') set at 3215'. Cement with 800 sacks "C" with 16% gel Gulfmix & 200 sacks "C" neat. Circulate cement. Plug down at 5:30 P.M., 8-5-80. WOC 18 hours. Test BOP & casing to 2000#, ok. Drilled float, cement & shoe. Start drilling 7-7/8" hole at 5:30 P.M., 8-6-80.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. L. Vaughn TITLE Area Drilling Supt. DATE 8-18-80

APPROVED BY John Runyan TITLE DATE AUG 19 1980

CONDITIONS OF APPROVAL IF ANY: