

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API No. 30-025-26777

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
B-1497

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER	7. Unit Agreement Name East Vacuum Gb/SA Unit
2. Name of Operator Phillips Petroleum Company	8. Farm or Lease Name East Vacuum Gb/SA Unit, Tract 2721
3. Address of Operator Room 401, 4001 Penbrook, Odessa, Texas 79762	9. Well No. 001
4. Location of Well UNIT LETTER M 100 FEET FROM THE West LINE AND 1150 FEET FROM South 27 TOWNSHIP 17-S RANGE 35-E N.M.P.M.	10. Field and Pool, or Wildcat Vacuum Gb/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3939.9' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPER. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	
		OTHER ☐ Total depth ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-11-80--MI Cactus Drlg. Spud in w/12-1/4" hole. Ran 8 jts of 8-5/8", 24#, K-55 csg. Set at 351'. Cmt w/400 sxs Class "H" w/2% CaCl₂, 1/4# Flocele. Circ 26 sxs to surface. Temp of cmt 60°, formation temp in zone 75°, cmt strength at time of csg test 1500#, time cmt in place, prior to test, 10-1/2 hrs. Test BOP's and csg w/1000 psi, OK. Drlg ahead w/7-7/8" bit.

6-22-80--Reached 4800' TD. Running logs.

6-24-80--Ran 118 jts 5-1/2", 14#, K-55 csg set at 4800'. Cmt w/900 sxs TLW w/12#/sx salt, 1/4#/sx Flocele, 10% DD, 3#/sx Gilsonite and 300 sxs Class "H" w/8#/sx salt. Circ 125 sxs to surface.

6-25-80--Release rig, prep to complete.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Senior Engineering Specialist DATE June 27, 1980

APPROVED BY Orig. Signed by Jerry Sexton TITLE Dist. 1. Supv DATE JUL 2 1980