

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

AMENDED to correct surface casing size/weight.

API NO. 30-025-26778

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
B-1497	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		7. Unit Agreement Name
2. Name of Operator		8. From or Lease Name
Phillips Petroleum Company		East Vacuum Gb/SA Unit
3. Address of Operator		9. Well No.
Room 401, 4001 Penbrook St., Odessa, Texas 79762		002
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>N</u> <u>2600</u> FEET FROM THE <u>West</u> LINE AND <u>1300</u> FEET FROM		Vacuum Gb/SA
THE <u>South</u> LINE, SECTION <u>27</u> TOWNSHIP <u>17-S</u> RANGE <u>35-E</u> N.M.P.M.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3931' GR		Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOBS ☒	
OTHER <u>Total depth</u> ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-5-80 MI Marc Drlg. Repairing rig.

6-9-80 Spud in w/12-1/4" hole. Ran 9 jts 8-5/8", 24#, K-55 csg set at 360'. Cmt w/400 sxs Cl "H" w/2% CaCl, 1/4#/sx Flocele. Circ 34 sxs to surf. Temp cmt slurry when mixed 60°, temp in zone 75°, est strength at time of testing 1500#. Cmt in place 11-1/2 hrs prior to test. Tested BOP's and csg 1000 psi, OK.

6-24-80 Reached 4800' TD. Running logs.

6-25-80 Ran 5-1/2", 14#, K-55 csg set at 4789'. Cmt w/400 sxs Cl "H" w/8#/sx salt and 1200 sxs TLW w/12#/sx salt, 1/4#/sx Flocele, 10% DD and 3#/sx Gilsonite. Circ 100 sxs.

6-26-80 Released rig--prep to complete.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

W. J. Mueller

TITLE Sr. Engineering Specialist

DATE March 13, 1981

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

skm