

STATE OF NEW MEXICO

ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

API No. 30-025-26779

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-1840-1

7. Unit Agreement Name

East Vacuum Gb/SA Unit

8. Field or Lease Name

East Vacuum Gb/SA
Unit, Tract 2739

9. Well No.

007

10. Field and Pool, or Wildcat

Vacuum Gb/SA

12. County

Lea

19. Elev. Casinghead

25. Was Directional Survey Made

No

27. Was Well Cored

AMOUNT PULLED

400 sxs Cl "H" w/2% CaCl₂, 14# Flocele.

Circd 45 sxs to surface.

1000 sxs TLW w/10% DD w/12# salt/sx,

(1/4#/sx Flocele, 3#/sx Gilsonite + 350 sxs Cl "H" w/5# salt. Circd 250 sxs to surface).

TUBING RECORD

PACKER SET

4641'

ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL

AMOUNT AND KIND MATERIAL USED

4338-4650'

Acidized w/17,900 gals 15%
NE HCl acid in 5 stages w/ball
sealers.

Well Status (Prod. or Shut-in)

Prod.

Gas - Oil Ratio

3941

Oil Gravity - API (Corr.)

37.9

Test Witnessed By

Don Thorpe

List of Attachments

Logs will be furnished direct by Schlumberger

I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief.

SIGNED *Ralph J. Rogers* W. J. Mueller

TITLE Sr. Engineering Specialist

DATE April 21, 1981

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 3a through 3d shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

Chinle _____ 224'	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
Rustler _____ 1610'	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
Salado _____ 1730'	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 2840'	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____ 3687'	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____ 4012'	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 4336'	T. Simpson _____	T. Gallup _____	T. Ignacio Quartz _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinley _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todillo _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Pennian _____	T. _____
T. Cisco (Dough C) _____	T. _____	T. Penn. "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____	No. 4, from _____ to _____
No. 2, from _____ to _____	No. 5, from _____ to _____
No. 3, from _____ to _____	No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
No. 2, from _____ to _____ feet
No. 3, from _____ to _____ feet
No. 4, from _____ to _____ feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1640	1640	Redbed				
1640	2884	1244	Anhy and Salt				
2884	3787	903	Anhy and Shale				
3787	3946	159	Anhy and Salt				
3946	4122	176	Anhy and Shale				
4122	4167	45	Dolo and Sand				
4167	4800	633	Lime and Shale				
4800	TD						

RECEIVED

APR 23 1981

OIL CONSERVATION DIV