Form 9-331 Dec. 1973

## UNITED STATES EPARTMENT OF THE INTERIOR

P. O. BOY 10		Form Approved. Budget Bureau No. 42-R1424
<b>r</b>	5. LEASE	
}	<b>5.</b> LEASE NM-4364	
VED	6. IF INDIAN, ALL	OTTEE OR TRIBE NAME

DEPARTMENT OF	THE INTERIOR
GEOLOGICAL	SURVERECEIVED

Dec 23 18 30 AM 83	7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELL'S	
Do not use this form for proposals to drill or to geopen or plug back taken different reservoir. Use Form 9-331-0 for such proposals 1 DUN. Least 1997 Art Publication	Young Deep 4 Federal  8. FARM OR LEASE NAME
ROSWELL CASTRICT	6. TAKMION EBIOLINAME
1. or gas en well well other	9. WELL NO.
2. NAME OF OPERATOR	10 SIELD OD WILLDOOT NAME
Harvey E. Yates Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	N. Young Bone Springs 11. sec. t. r., m., or blk. and survey or
P. o. Box 1933, Roswell, New Mexico 88201	AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below)	Sec. 4, T-18S, R-32E
AT SURFACE 660' FSL & 1980' FEL	12. COUNTY OR PARISH: 13. STATE
AT TOP PROD. INTERVAL:	Lea NM.
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	3862 GL
REQUEST FOR APPROVAL TO. SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOCT OR ACIDIZE	(NOTE: Report results of multiple completion or zone
SHOCT OR ACIDIZE  SHOCT OR ACIDIZE  REPAR WELL  PULL OR ALTER CASING  MULTIPLE COMPLETE  CHANGE ZONES  ABANDON*	change on Form 9-330.)
MULTIPLE COMPLETE	
CHANGE ZONES	
ABANDON = = = =	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is comeasured and true vertical depths for all markers and zones pertine	directionally drilled, give subsurface locations allo
3/14/83 RU BD well, unseat pkr & pull 8300' tbg.	Run 5 jts tbg, put on tbg anchor
Run 3500' tbg. 9/15/83 Fin running 2 3/8" tbg to 8475'. Set tb	g @ 8320', run 2" X 1 1/4" X 20' pump,
9/15/83 Fin running 2 3/8" tbg to 84/5". Set tb 218 3/4 rods, 119 7/8" rods. Hang on ja	ck.
9/16/83 RD & Put well on production.	
•	
Subsurface Safety Valve: Manu, and Type	
18. I hereby cortify that the foregoing is true and correct	December 21, 1983
SIGNED ACCEPTED FUNDICULARIE Res. Engine	
HW (1) (This space for Federal or State (	unice use/
CONDITIONS OF APPROVAL MAYIN 9 1984	DATE

(alstal), NEW MEXICO

MAY 1 0 1984
HOSES OFFICE