

PHILLIPS PETROLEUM COMPANY--PERMIAN BASIN AREA

SWD/INJECTION WELL DATA SHEET

RKB @ 3978.7
 CHF @ 11.7
 GL 3967

Date 08-20-91

District NORTH Subdistrict EVGSAU
 Lease & Well No. EVGSAU #3127-W005 API No.: 30-025-26862
 Legal Description 10' FSL, 10' FEL, SEC. 31
T-17-S, R-35-E, LEA COUNTY State: NEW MEXICO

Field: VACUUM GB/SA Formation: GB/SA
 Well Classification: INJECTION Status: ACTIVE

Average Injection Volume: BMPD Average Reservoir Pressure 2083 psi

Normal H2O Inj. Pressure: 320 psi Authorized H2O Inj. Pressure: 1350 psi

Permitted Injection Interval: 4350' to 4800' (TD) OR BASE SA
 Completed Injection Interval: 4352' to 4682'

Date Well Drilled: 7-28-80 Date Converted to Inj/SWD: 12-8-80

CBL Run? Yes: No: X Is it available? Yes: No:

Temp Survey Run? Yes: No: X Is it available? Yes: No:

TAKEN ON 06/02/93
 16" H-40 Csg @ 360'
 TOC @ SURFACE

10 3/4" 40.5# K-55Csg @ 1450'
 TOC @ SURFACE

Injection well pressure measurement method: GAUGE
 Frequency of pressure measurement: WEEKLY - MONTHLY

Does well have any plugging tendency? Yes: X No:
 If so, how often? FIVE YEARS

Date of last H5 or Mechanical Integrity Test: 01-13-89
 Required Test Frequency:

Has well ever failed an H5 or Mechanical Integrity Test? Yes: No: X
 If so:

When?
 Why?
 How was it corrected?

Does well penetrate any usable water source? Yes: X No:
 If yes, then:

Name of usable water source: OGALLALA/SANTA ROSA
 Depth to top of the source: 0 Feet
 Depth to bottom of source: 1530 Feet

2-7/8" J-55 IPC Tbg @ 4263'
 BAKER LOC-SET
 BAKER LOC-SET Pkr @ 4263'

Top of GB/SA @ 4050'
 Perfs: 4352'- 4682'
 119'-119 HOLES

5-1/2" 14# K-55 Csg @ 4796'
 TOC @ SURFACE

TD:4800'
 PBSD:4750'

Checked by:
 Prod. Engr.
 Resv. Engr.

File name H:\INJECTOR\EVGSAU\3127005.INJ

