STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

THO I AND ITM TENALS DE		11416
HO. OF COPIES SECEIVED		
DISTRIBUTION		
SANTA FE		
FILE	T_{-}	
U.S.O.S.		
LAND OFFICE		
OPERATOR	1	

OIL CONSERVATION DIVISION P. O. BOX 2088

Form C-103 . Revised 10-1-78

SANTA FE, NEW MEXICO 87501	
FILE	5a. Indicate Type of Lease
U.S.G.S.	State X Fee
OPERATOR	5. State Oil & Gus Lease No.
API NO. 30-025-26864	B-1527
	vinninininink
SUNDRY NOTICES AND REPORTS ON WELLS [DO NOT USE THIS FORM FOR PROPOSALS TO DRILL ON TO DEEPLH OR PLUG BACK TO A DIFFERENT RESERVOIR. "SE "APPLICATION FOR PERMIT _" (FORM C-101) FOR SUCH PROPOSALS.)	
on GAB OTHER Water Injection	7. Unit Agreement Name East Vacuum Gb/SA Unit
Name of Operator	8. Form or Lease Name East Vacuum
Phillips Petroleum Company	Gb/SA Unit, Tract 3127
Room 401, 4001 Penbrook, Odessa, Texas 79762	007
i, Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER J 2560 FEET FROM THE SOUTH LINE AND 2550 FEET FROM	Vacuum Gb/SA
East Line, Section 31 TOWNSHIP 17-S RANGE 35-E NMPM	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea
Check Appropriate Box To Indicate Nature of Notice, Report or Ot	her Data
	T REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON . COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING CASING TEST AND CEMENT JOS X	, rece and againstant
	ater Injection X
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703.	g estimated date of starting any proposed
07-12-80MI Cactus Drlg. Spudded w/26" bit at 11:00 PM. Drld ahead.	
07-13-80Drld to 351'. Prep to run 16" csg.	
07-14-80Ran 16", 68#, K-55 csg set at 349'. Cmtd w/1123 sxs Class "]	H" cmt. 2% CaClo 1/4#/sv
Flocele. Circ 327 sxs to surface. WOC 18 hrs. Tstd csg and ahead $w/14-3/4$ " bit.	d BOP 1000#, OK. Dr1d
07 16 90 Par 10 2/48 40 E# 77 EE	ad that
07-16-80Ran 10-3/4", 40.5#, K-55 csg set at 1448'. Cmtd w/1500 sxs of Flocele. Circ 425 sxs to surface. WOC 8 hrs. Tstd csg and ahead w/7-7/8" bit.	CI "H", w/2% CaCl ₂ , 1/4#/sx BOP 1000#, OK. Dr1d
07-26/27Drld to 4818' TD. Logged. -80	
07-28-80Ran 5-1/2", 14#, K-55 csg set at 4815'. Cmtd w/1200 sxs TLW 1/4#/sx Flocele, 3#/sx gilsonite followed w/450 sxs Cl "H" w, sxs. WOC 8 hrs.	w/10% DD, 12#/sx salt, /5#/sx salt. Circ 350
Released rig, prep to complete.	
8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Regul J. Rogert W. J. Mueller TITLE Senior Engineering Special:	ist DATE August 18, 1980
Cate Signed by	
PPROVED BY SEED 3 TITLE	OATE ALDER STEELINGER