

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	For <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Amoco Production Company		8. Farm or Lease Name Robinson Com.
3. Address of Operator P. O. Box 68 Hobbs, NM 88240		9. Well No. 1
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>14</u> TOWNSHIP <u>19-S</u> RANGE <u>35-E</u> N.M.P.M.		10. Field and Pool, or Wildcat Wildcat Morrow
15. Elevation (Show whether DF, RT, GK, etc.) 3764.9 GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a TD of 5900' and ran 17# 17-80 9-5/8" casing set at 5900'. Cemented with 2900 SX BJ Light cement (with 18% salt, 5# Gilsonite/SX and 1/4# Flocele/SX) and with 200 SX Class C cement (with 1/4# Flocele/SX). Plugged down at 8:00 p.m. 8-27-80. Cement did not circulate. Ran temp survey. Top of cement at approx. 870'. WOC 18 hr. Tested casing with 1000# for 30 min. Test OK. Reduced hole to 8-3/4" and resumed drilling.

0+4-NMOCD

1-Hou

1-Susp

1-LBG

1-W. Stafford, Hou

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Administrative Analyst DATE 9-10-80

Orig. Signed by
John Runyan
Geologist

APPROVED BY _____ TITLE _____ DATE _____

SEP 12 1980

CONDITIONS OF APPROVAL, IF ANY: