

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LG - 3230

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (Form C-101, FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐
Name of Operator
InterNorth, Inc.
Address of Operator
403 Wall Towers West, Midland, Texas 79701
Location of Well
UNIT LETTER J, 1980 FEET FROM THE South LINE AND 2200 FEET FROM
THE East LINE, SECTION 32 TOWNSHIP 19S RANGE 33E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name
Tonto State Com.
9. Well No.
1
10. Field and Pool, or Wildcat
Undesignated Gem
(Morrow)
12. County
Lea

15. Elevation (Show whether DF, RT, GR, etc.)
3569.5' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-30-81 Drilled to 5210'.

Ran 33 jts. (1478.32') 8-5/8" S-80 ST & C csg. equipped w/float shoe & float collar, 83 jts. (3245.57') 28# K-55 ST & C csg. equipped w/Lynes ECP & Dowell D.V. Tool, and 10 jts. (486.11') 24# K-55 ST & C csg. (Total of 5210'). Set 8-5/8" csg. @ 5210' & cemented w/1000 sx 50/50 Poz & 4% D20 & 10# D24 & 15# D44 & 40# D29 and tailed in w/200 sx Class 'C' cmt. Neat. Plug down @ 10:15 p.m. 6-30-81. Opened D.V. Tool & circulated while WOC.

7-1-81 Cemented 2nd stage w/1400 sx 50/50 poz & 4% D20 & 10# D24 & 15# D44 & 1/4# D29 & 2% S-1 and tailed in w/100 sx Class 'C' cmt. & 2% CaCl. No cmt. to surface. PD @ 8:30 a.m. 7-1-81. Ran Temperature Survey, indicated top of cmt. @ 1360'.

7-3-81 Drilled D.V. Tool & tested to 1500#, okay.

7-4-81 Drilled out to 6050'.

7-8-81 Cemented outside of 8-5/8" casing through 1" from 1380' to surface. Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E.H. Foret E.H. Foret TITLE District Engineer DATE 9-30-81

ORIG. SIGNED BY Jerry Sexton
PROVED BY Dist. 1, Supv. TITLE _____ DATE 10-2-81

CONDITIONS OF APPROVAL, IF ANY: