

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

API No. 30-025-26194

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
B-1399-10

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator	East Vacuum GB/SA Unit
3. Address of Operator	8. Farm or Lease Name
Room 401, 4001 Penbrook St., Odessa, Texas 79762	East Vacuum GB/SA Unit, Tract 2913
4. Location of Well	9. Well No.
UNIT LETTER 0 1150 FEET FROM THE South LINE AND 2500 FEET FROM East THE LINE, SECTION 29 TOWNSHIP 17-S RANGE 35-E N.M.P.M.	009
15. Elevation (Show whether DF, RT, GR, etc.)	10. Field and Pool, or Wildcat
3968' GR	Vacuum Gb/SA
	12. County
	Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPS. ☒	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒	
OTHER Total Depth ☒	

17. Describe the Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.


11-30-80 MI Cactus Drlg. Spud w/11" bit to 365'. Ran 8-5/8", 24#, K-55 csg set at 365'. Cmdt w/400 sxs C1 "H" w/2% CaCl₂. Circd 100 sxs surf. Tstd csg 12 hrs after plug down. Temp of cmt 45°, formation temp in zone 63°, cmt strength at time of csg test 960 psi, time cmt in place prior to test 12 hrs. Tstd csg and BOP 1000#, OK. Drld ahead w/7-7/8" bit.

12-9-80 Drld to 4800' TD. Logged.

12-10-80 Ran 5-1/2", 15.5#, K-55 csg set at 4793'. Cmdt w/1100 sxs TLW w/12#/sx salt, 10% DD, followed w/400 sxs C1 "H" w/5#/sx salt. Displaced plug w/20 bbls Acetic acid and 94 bbls FW. Max press before plug bmpd, 1400#. Bmpd plug w/2000#, OK. Circd 140 sxs to surface.


12-11-80 Released rig--prep to complete.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED  W. J. Mueller

TITLE Sr. Engineering Specialist

DATE December 22, 1980

APPROVED BY  Les Clement

TITLE

DATE DEC 29 1980

CONDITIONS OF APPROVAL, IF ANY:

aj