(May 1963) DEPARTMENT OF THE INTERIOR (Other Instructions of	5. LEASE DESIGNATION AND SERIAL NO.
GEOLOGICAL SURVEY HOBBS, NEW MEXICO SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT_" for such proposals.)	6. IF INDIAN, ALLOTTEE OR THIBE NAME
	7. UNIT AGREEMENT NAME
WELL WELL OTHER 2. NAME OF OPERATOR	S. FARM OR LEASE NAME
AMINOIL USA, INC.	Federal 30
3. ADDRESS OF OPERATOR	9. WELL NO.
P.O. Box 10525, Midland, Texas 79702	1
 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 	10. FIELD AND POOL, OR WILDCAT Wildcat
1980' FSL & 760' FEL of Sec. 30, T-19-S,R-33E	11. SEC., T., E., M., OE BLK. AND SURVEY OR AREA
	Sec. 30, T-19-S,R-33-E
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OF PARISH 13. STATE
Setp. 23, 1980 3585.6 GR	Lea N.M.
16. Check Appropriate Box To Indicate Nature of Notice, Report,	or Other Data
NOTICE OF INTENTION TO:	UBSEQUENT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING	ement intermediate
REPAIR WELL CHANGE PLANS (Other) Run & Cement intermediate X (Other) Run & Cement intermediate X	
 17. DESCRIBE INDPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent proposed work. If well is directionally drilled, give subsurface locations and measured and true nent to this work.)* 	dates, including estimated date of starting any
<pre>Drill 12 ½" hole from 1276' to 5310', Circulated & conditioned 126 jts. (5314.84') 9 5/8" casing 76 jts. (3265.95') 9 5/8" 36#, K-55, ST&C 23 jts (863.00') 9 5/8", 40#, K-55, ST&C 27 jts. (1178.78') 9 5/8", 40#, N-80, LT&C Set @ 5310'. Cemented 9 5/8" csg w/580 sx Halliburton Light f Place have the 20 A M = 7 7 81 = 1000 AW POPle 5 tested to 5000#</pre>	followed by 250 0 sx class "C",
Plug down at 1:20 A.M. 7-7-81. WOC, NU BOP's & tsted to 5000 , Hydril to 1500 , OK, tstd casing to 1500 , ok. WIH & began drilling out cement & new formation. CiRC,	
	DECEN//
2	OIL & GAS U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO
18. I hereby certify that the foregoing is true and correct SIGNED ACCEPTED FOR RECORD	1gr. DATE 9-18-81
(This space for Federal & State block MeAN APPROVED BY	DATE
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO *See Instructions on Reverse Side	

RECEIVED SEP 2.8 1981