

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
reverse side)

re-

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0141013

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Pennzoil Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT Undesig.

Quail Ridge Morrow Gas

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 19, T-19-S, R-34-E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

1. OIL ☐ GAS ☒ OTHER

2. NAME OF OPERATOR

WILLIAM N. BEACH

3. ADDRESS OF OPERATOR

Post Office Box 3669, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with applicable requirements. See also space 17 below.)
At surface

660' FNL and 2030' FEL of Section 19

U. S. GEOLOGICAL SURVEY

HOBBS, NEW MEXICO

14. PERMIT NO.

*

15. ELEVATIONS (Show whether of, to, or from sea level)

3705.3 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing and Cementing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well spud on December 21, 1980.

17 1/2" Hole.

Ran 10 jts (407.48'), 13 3/8", 54.50#, K-55, ST&C casing. Set casing at 405'.

Cemented with 450 sacks Class "C" w/2% CaCl. Plug down at 12:15 AM, December 23, 1980. Cement circulated.

Top of cement behind casing - surface.

Depth of cementing tools - 405'.

Tested with rig pump, 1000 psi for 30 minutes - no pressure loss.

* Date of Application to Drill is August 22, 1980. This application was received by U.S.G.S. on August 25, 1980. Permit No. not available.

18. I hereby certify that the foregoing is true and correct

SIGNED

William N. Beach

TITLE Agent

DATE December 31, 1980

(This space for Federal or State official use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

JAN 6 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side