

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API No. 30-025-27115

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-1492

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

7. Unit Agreement Name
East Vac-Gb/SA Unit

Name of Operator
Phillips Petroleum Company

8. Farm or Lease Name
SA Unit
East Vac-Gb/Tract #2622

Address of Operator
Rm. 401, 4001 Penbrook St., Odessa, Texas 79762

9. Well No.
005

Location of Well
UNIT LETTER C 340 FEET FROM THE North LINE AND 2300 FEET FROM
THE West LINE, SECTION 26 TOWNSHIP 17-S RANGE 35-E NMPM.

10. Field and Pool, or Wildcat
Vacuum Gb/SA

15. Elevation (Show whether DF, RT, GR, etc.)
3910 Gr 3,922 RKB

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐
PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOBS ☒
OTHER ☐ Total Depth ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1-23-81 MI Cactus Drlg. Spud w/12-1/4" bit. Howco cmtd 8-5/8" csg @ 365' w/400sxs Cl "C" cmt w/2% CaCl₂ & 1/4# Flocele/sx. Circ. 100 sxs to surface. Temp cmt 50°F; formation temp, 65°F; cmt strength at time of csg test, 610 psi; cmt in place 14 hrs prior to test. Test csg & BOP, 600#. Drld ahead w/7-7/8" bit.
- 1-24/2-5-81 Reached drillers TD, 4800'. Running logs.
- 2-6/2-8-81 Logging. Ran 5-1/2", 14#, K-55 csg. set @ 4800'. CmV w/800 sxs TLW w/12#/sx salt, 10% DD, 3# sxs Gilsonite, 1/4#/sx Flocele, 400 sxs Cl "C" cmt w/6# salt. Circd 248 sxs to surface.
- 2-9-81 Released rig; prep to complete

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W.J. Mueller

TITLE Sr. Engineering Specialist

DATE

APPROVED BY

TITLE

DATE

ADDITIONS OF APPROVAL, IF ANY