

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR
Union Oil Company of California

3. ADDRESS OF OPERATOR
P. O. Box 671 Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FSL 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐ Set Production Casing

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-12-81 WOC 24 hrs. Drld 8-3/4" hole from 3,100' - 12,174' @ 3:15 AM 10-21-81. Schlumberger ran CNL FDC W/GR 12,170' to surface & DLL W/Micro SFL from 12,160' - 3,100'. Ran 292 jts. & 1 pc (12,150') 7" OD 26# S-95 & N-80 casing @ 12,174' w/float collar @12,088' DV tool @ 8,512' & 3,406' cemented 1st stage around shoe w/400 sx lite water followed w/600 sx Class "H". Opened DV tool @ 8,512' cir 300 sx to pit. Cemented 2nd stage w/1,400 sx lite water, closed DV tool @ 3,512' - opened DV tool @ 3,406' and cir 450 sx. Cemented 3rd stage thru DV tool @ 3,406' w/600 sx lite water and 100 sx class "C" neat, closed DV tool @ 3,406' w/3000 psi cir 173 sx. Job complete 3:20 AM 10-24-81. WOC

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN
FOR ROGER A. CHAPMAN

TITLE Dist. Drilling Supt. DATE 10-27-81

(This space for Federal or State office use)

APPROVED BY NOV 16 1981
CONDITIONS OF APPROVAL, IF ANY

TITLE _____ DATE _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

RECEIVED
JUL 17 1981