REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

, Dec., 1973	Budget Bureau No. 42-R1424
. UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-34850
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepfor proposals of a different reservoir. Use Form 9–331–C for such proposals.)	B FARM OR LEASE NAME
1. oil gas well other	Federal BU  9. WELL NO.
2. NAME OF OPERATOR FEB 19 1981	J. WELLING.
Amoco Production Company	10. FIELD OR WILDCAT NAME
3 ADDRESS OF OPERATOR U.S. GEULUGICAL	SUIENST Gem Morrow
P. O. Box 68 Hobbs, NM 88240BBS, NEW MI	XICOSEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	27-19-33
AT SURFACE: 1980' FSL & 1980' FEL, Sec. 22	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: (Unit J, NW4/, SE/4) 2/	Lea NM
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	3585.7' GL
DECLIFOR FOR ADDROUGH TO: CURREQUENT DEDOOR OF	

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

MULTIPLE COMPLETE CHANGE ZONES ABANDON\* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Tagged fish at approx. 2573' on 2-13-81. Set a 150-sack Thickset cement plug at 2545'. WOC 8 hr. Tagged top of cement at 2505'. SPotted 135 sacks Class C cement with 2% CaCl. Tagged cement at 2424' and spotted 660 sacks Lite cement. Tagged cement at 1862' and spotted 660 sacks Lite cement. Tagged cement at 1208' and spotted 345 sacks Lite cement. Tagged cement at 526' and spotted 100 sacks Class C cement with 2% CaCl. Tagged top of cement at 93' and cemented to surface with 35 sacks Class C cement with 2% CaCl. Will install P X A marker and clean up location upon completion of Federal BU No. 1-Y. 0+4-USGS . H 1-Hou 1-Susp 1-LBG 1-W. Stafford, Hou

SUBSEQUENT REPORT OF:

18. I hereby pertify that the foregoing is true and correct

APPROVED (Prig. Sed.) PETER W. CHESTER TILE

DATE

Set @ \_

APPROVED (This

CONDITIONS OF APPROVAL, IF ANY:

Subsurface Safety Valve: Manu. and Type

NOV 3 0 1982

FOR

SIGNED

JAMES A. GILLHAM DISTRICT SUPERVISOR

e Instructions on Reverse Side

TITLE Ast. Adm. Analyst