## STATE OF NEW MEXICO NERGY AND MINERALS DEPARTMENT

wo, ar cortes necessed	.l	
ногтивитыя		
SANTA FE		
PILE		
U.S.G.S.	_l	
LAND OFFICE		
OPERATOR		

PILE	S	P. O. BOX 2088 ANTA FE, NEW MEXICO 87501	. Revised 19-1-78
U.S.O.S.  LAND OFFICE  OPERATOR	E .	•	State Oil & Gas Lease No.
{DO HOY U3E	7. Unit Agreement Name		
Name of Operator	WELL OTHER-		8. Farm or Lease Naine
DAVID FASKEN Address of Operator			Consolidated State
608 First	or National Bank Building	g, Midland, TX 79701	1
Location of Well		ROM THE NORTH LINE AND 330 FEET FRO	Midway (Devonian)
West		TOWNSHIP 17-S RANGE 37-E NMPP	
15. Elevation (Show whether DF, RT, GR, etc.)  3784.30 GL			12. County Lea
	Check Appropriate E	ox To Indicate Nature of Notice, Report or O subsequer	ther Data
EMPORABILY ABAND JUL OR ALTER CAS!	OON O	PLUG AND ABANDON REMEDIAL WORK  COMMENCE DRILLING OPHS.  CASING TEST AND CEMENT JQB  OTHER	ALTERING CASING PLUG AND ABANDONMENT
work) SEE RUL	E 1 (03.	state all pertinent details, and give pertinent dates, includi	
<u>1-10-81</u> <u>1-11-81</u>	Ran 13-3/8" H-40 48# S + 100 sx Class "C" w/2	/17½" bit, drilled to 398' KB. T&C csg & set @ 398' KB. Cemented w/ % CaCl. Bumped plug to 800# @ 5:30 a	.m. 1-11-81. S1 @
	Ran 13-3/8" H-40 48# S + 100 sx Class "C" w/2		.m. 1-11-81. S1 @
	Ran 13-3/8" H-40 48# S + 100 sx Class "C" w/2 surface. WOC 24 hrs.	T&C csg & set @ 398' KB. Cemented w/ % CaCl. Bumped plug to 800# @ 5:30 a	.m. 1-11-81. S1 @
	Ran 13-3/8" H-40 48# S + 100 sx Class "C" w/2 surface. WOC 24 hrs.	T&C csg & set @ 398' KB. Cemented w/ % CaCl. Bumped plug to 800# @ 5:30 a	.m. 1-11-81. S1 @
	Ran 13-3/8" H-40 48# S + 100 sx Class "C" w/2 surface. WOC 24 hrs.	T&C csg & set @ 398' KB. Cemented w/ % CaCl. Bumped plug to 800# @ 5:30 a	.m. 1-11-81. S1 @
1-11-81	Ran 13-3/8" H-40 48# S + 100 sx Class "C" w/2 surface. WOC 24 hrs. cement.	T&C csg & set @ 398' KB. Cemented w/% CaCl. Bumped plug to 800# @ 5:30 a Commenced drilling @ 6:00 a.m. 1-12-	.m. 1-11-81. S1 @
1-11-81	Ran 13-3/8" H-40 48# S + 100 sx Class "C" w/2 surface. WOC 24 hrs. cement.	T&C csg & set @ 398' KB. Cemented w/ % CaCl. Bumped plug to 800# @ 5:30 a	.m. 1-11-81. S1 @
1-11-81	Ran 13-3/8" H-40 48# S + 100 sx Class "C" w/2 surface. WOC 24 hrs. cement.	T&C csg & set @ 398' KB. Cemented w/% CaCl. Bumped plug to 800# @ 5:30 a Commenced drilling @ 6:00 a.m. 1-12-	.m. 1-11-81. S1 @