

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil well ☒ gas well ☐ other ☐

APR 23 1981

2. NAME OF OPERATOR

Harvey E. Yates Company U.S. GEOLOGICAL SURVEY

3. ADDRESS OF OPERATOR

HOBBS, NEW MEXICO

P. O. Box 1933, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Spud, Surface Casg & Csg Test

5. LEASE

LC-064009-D

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Young Deep Unit

8. FARM OR LEASE NAME

9. WELL NO.

4

10. FIELD OR WILDCAT NAME

N. Young Bone Springs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 9, T-18S, R-32E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3828.3' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4/11/81 Depth-650' cementing csg. SPUDDED @ 7:30 a.m. 4/10/81.

Formation-Rd Beds: spud mud in hole: Ran 16 jts 13 3/8", 54.5#, ST&C, H-40 csg (653.56') and set @ 650'. Cemented w/750 sx Class "C" w/2% CaCl/sx. Circ 70 sx; bumped plug @ 5:30 a.m. w/600 psi - held o.k.

4/12/81 Depth-942'. Formation-Anhy; drlg w/brine water; 292' of progress. Tested BOP & casing to 1000 psi.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Paul Harder*

TITLE Engineer

DATE April 21, 1981

ACCEPTED FOR RECORD  
ROGER A. CHAPMAN

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

AUG 28 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side