

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

*NOTE: Submitted to amend casing seat.

API No. 30-025-27304

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐

GAS WELL ☐

OTHER

Water Injection

Name of Operator

Phillips Petroleum Company

Address of Operator

Room 401, 4001 Penbrook St., Odessa, Texas, 79762

Location of Well

UNIT LETTER M 1300 FEET FROM THE south LINE AND 50 FEET FROM

THE West LINE, SECTION 22 TOWNSHIP 17-S RANGE 35-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3940.5 Gr (unprepared)

5a. Indicate Type of Lease

State ☒

Fee ☐

5. State Oil & Gas Lease No.

B-1585-5

7. Unit Agreement Name East

Vacuum Gb/SA Unit

8. Farm or Lease Name East

Vacuum Gb/SA Unit, Tract

2230

9. Well No. 004

10. Field and Pool, or Wildcat

Vacuum Gb/SA

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

FULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☒

OTHER

Total Depth ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-17-81: Cactus Drlg spudded w/12-1/4" bit to 381' at 5:30 p.m. Ran 8-5/8", 24#, K-55 csg set at 381'. Cmt w/800 sxs Cl "C" cmt w/2% CaCl₂, 1/4# sx Flocele. Circd 8 sxs. Tested csg 14 hrs after plug down; temp. cmt. slurry, 55°; Temp in formation, 64°; Estimated csg strength at time of csg test exceeds 500 psi. Time cmt in place prior to test 14 hrs. Drld ahead w/7-7/8" bit.

3-18/3-28-81: Reached TD of 4800'. Ran logs.

3-29/3-30-81: Ran 4-1/2", N-80, 11.6# csg set at 4785'. Cmt w/800 sxs TLW w/12# sx salt, 10% DD, 3# sx Gilsonite, 1/4# sx Flocele, followed w/400 sxs Cl "C" w/6# sx salt. Circd 200 sxs.

3-31-81: Released rig. Prep to complete.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Sr. Engineering Specialist

DATE April 10, 1981

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

:ehg