

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API No. 30-025-27316

5a. Indicate Type of Lease
State ☒ For ☐
5. State Oil & Gas Lease No.
B-2224

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐	GAS WELL ☐	OTHER - ☒ Water injection
Name of Operator		
Phillips Petroleum Company		
Address of Operator		
4001 Penbrook, Rm. 401, Odessa, Texas 79762		
Location of Well		
UNIT LETTER	A	50 FEET FROM THE North LINE AND 50 FEET FROM
THE East	LINE, SECTION 28	TOWNSHIP 17-S RANGE 35-E N.M.P.M.

7. Unit Agreement Name
East Vacuum Grayburg-San Andres Unit
8. Farm or Lease Name
East Vacuum Grayburg-SA Unit, Tr. 2851
9. Well No.
002
10. Field and Pool, or Wildcat
Vacuum GB/SA
12. County
Lea

15. Elevation (Show whether DF, RT, GR, etc.)

3946.1 Gr. (Unprepared)

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOBS ☒	
OTHER ☒ Total Depth	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 4-9-81 Cactus Drlg spudded w/12-1/4" bit to 371' @ 10:30 AM. Ran 8-5/8", 24#, K-55 csg to 371'. Cmt'd w/400 sxs Class "C" w/2% CaCl₂ & 1/4# sx Flocele. Circ'd 40 sxs cmt. Tstd csg 16 hrs after plugdown; Temp of cmt, 65°; formation temp in zone, 60°; cmt strength @ time of csg test exceeds 500 psi; time cmt in place prior to test, 16 hrs. Drl'd ahead w/7-7/8" bit.
- 4-10/4-19-81 Reached total depth of 4800'.
- 4-20-81 Ran 4-1/2" 11.6#, N-80 csg set @ 4800'. Cmt'd csg w/1000 sxs TLW, 10% DD, 12#/sx salt, 1/4#/sx Flocele, 3#/sx Gilsonite, followed w/400 sxs Class "C" w/6#/sx salt. Circ'd 165 sxs. Released rig; prep to complete.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ralph J. Rapier for W.J. Mueller TITLE Sr. Engineering Specialist DATE April 21, 1981

APPROVED BY Jerry Smith
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE APR 24 1981