

Santa Fe, New Mexico

JUN - 1 1950

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Box 670

Roswell, New Mexico May 29, 1950

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,


Place

Date

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as
Barnett & Rector State "N" well No. **2** in **NW 1/4**

Company or Operator **Vacuum** Lease **Lea** County.
of Sec. **20**, T. **17S**, R. **35E**, N. M., P. M., **1650** Field, **South** line and **660** feet
N The well is **1650** feet (N.) **(S.)** of the **South** line and **660** feet
(E.) **(W.)** of the **West** line of **Sec. 20**



AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows:
Rotary to about 1800'; Cable tools from about 1800' to about 4700'

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the
Commission is as follows: **Blanket bond already filed**

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
0-250) 13"	8 5/8"	28#	New	1800	Cemented	(75 on bottom & 100 from 250' back to surface)
(250-1800) 11"	7" CD	20#	New	4350	Cemented	100

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about **4450** feet.

Additional information: **The 8 5/8" casing will be cemented with not less than 75 sacks of cement at the bottom; then a string of 1" pipe will be run down to 250' on the outside of the 8 5/8" casing, and cement circulated from that point on back to surface.**

Approved JUN 1 1950, 19____
except as follows:

Sincerely yours,

Barnett & Rector

Company or Operator

By John A. Barnett

Position

Send communications regarding well to:

Name **Barnett & Rector**

Box 670

Address **Roswell, New Mexico**

OIL CONSERVATION COMMISSION

By Ray YurkovichTitle Oil & Gas Inspector