

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Southland Royalty Company		8. Farm or Lease Name Scharb "9"
3. Address of Operator 1100 Wall Towers West Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>9</u> TOWNSHIP <u>19-S</u> RANGE <u>35-E</u> N.M.P.M.		10. Field and Pool, or Wildcat Undesignated (Wolfcamp)
15. Elevation (Show whether DF, RT, GR, etc.) 3843.5' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <u>Set 11 3/4" surface csg</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17 1/2" hole @ 12 noon 7/20/81. Drill to 406'. Ran 11 jts 11 3/4" 42# H-40 ST&C csg (414'). Set @ 406'. Cmt w/450 sxs C1 "C" w/2% CaCl₂. PD @ 11:40 PM 7/20/81. Circ 60 sxs cmt. WOC 18 hrs. Install BOP. After 24 hrs, test csg & BOP to 1000# for 30 min. Held okay. Drill ahead w/11" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u>Ray</u>	TITLE <u>Engineering Tech.</u>	DATE <u>7/23/81</u>
APPROVED BY <u>Don</u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		