

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

WOCO 88240

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL X 1980' FWL, Sec. 11

AT TOP PROD. INTERVAL: (Unit K, NE/4, SW/4)

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Set production casing

5. LEASE

NM-40452

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal BS Gas Com.

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Und. Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

11-18-32

12. COUNTY OR PARISH

Lea

13. STATE

NM


14. API NO.

30 025 27430

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3867.8 RDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On 8-23-81 ran 3060' of 20# S-95, 3920' of 17# N-80 and 6320' of 20# N-80 5-1/2" production casing. Set at 13470'. Cemented in 2 stages with DV tool set at 7997'. Cemented first stage with 2070 sacks of Class H cement containing 1.15% CF-9 and 2% KCL. Circulated 178 sacks. Cemented second stage with 750 sacks of Lite containing 5#/sack of salt, 1/2 #1 sack of Cello-seal and tailed in with 100 sacks of Class H. Plug down at 11:15 a.m. 8-24-81. Cement did not circulate. Ran temperature survey and TCMT 4900' from surface. WOC 18-1/2 hrs. Pressure tested to 950 psi for 30 min. Tested OK. Released rig 8-26-81. Currently waiting on completion unit.

0+4-USGS 1-Hou 1-Susp 1-W. Stafford, Hou 1-MDR 1-EI Paso Ex.  
Subsurface Safety Valve: Manu. and Type Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Mark Randolph

TITLE

Ast. Adm. Analyst

DATE

8-28-81

ACCEPTED FOR RECORD

ROGER A. CHAPMAN

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY

SEP 2 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side