

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 1980' FWL

AT TOP PROD. INTERVAL: Sec. 11 (Unit K, NE/4,

AT TOTAL DEPTH: SW/4)

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐


MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 7-1-81 ran 9.625" 40# N-80 casing set at 4900'. Cemented with 2900 sacks of lite containing 15#/sack salt, 5#/sack Gilsonite, 1/4#/sack Cello-seal, and tail in with 200 sacks Class C cement containing 1/4#/sack Cello-seal. W.O.C. for 18 hrs. Tested casing to 1000# psi for 30 min. Tested OK. Reduced hole to 8-3/4" and resumed drilling.

0+4-USGS

1-Hou

1-Susp

1-MDR

1-W. Stafford, Hou

1-El Paso Ex.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mark Randolph TITLE Ast. Adm. Analyst DATE 8-4-81

ACCEPTED FOR RECORD
ROGER A. CHAPMAN (This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side