

OPERATOR'S COPY

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Box 68 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL X 1980' FWL, Sec. 11

AT TOP PROD. INTERVAL: (Unit K, NE/4, SW/4)

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

JUN 29 1981

U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Report results of multiple completion or zone change on Form 9-330.)

5. LEASE

NM-40452

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME

Federal BS Gas Com.

1981

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Und. Morrow

RECEIVED

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

11-18-32

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3841.8' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 6-9-81 Kenai Drilling Rig #23 spudded a 17-1/4" hole at 7:00 p.m. Drilled to a TD of 672'. Ran 13-3/8" 48# H-40 casing set at 672'. Cement with 700 SX Class C cement with 1% CaCl. Plugged down 10:30 p.m. 6-16-81. Circulated 15 SX. WOC 18 hrs. Tested casing to 1000# for 30 min. Tested OK. Reduced hole to 12-1/4" and resumed drilling.

0+4-USGS 1-Hou 1-Susp 1-MKE 1- W. Stafford, Hou
1-El Paso Exploration

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Admin. Analyst

DATE

6-24-81

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD (This space for Federal or State office use)
ROGER A. CHAPMAN

TITLE

DATE

JUL 2 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side