

N. M. OIL FIELD COMMISSION  
P. O. BOX 1983  
HOBBS, NEW MEXICO 88240

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

RECEIVED

DEC 23 10 44 AM '83

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR  
Harvey E. Yates Company
3. ADDRESS OF OPERATOR  
P. O. Box 1933, Roswell, NM 88201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE 1980' FSL & 1980' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other) Perf	<input type="checkbox"/>

5. LEASE  
NM-036852
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Young Deep 3 Federal
9. WELL NO.  
#3
10. FIELD OR WILDCAT NAME  
N. Young Bonesprings
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 3, T-18S, R-32E
12. COUNTY OR PARISH 13. STATE  
Lea NM
14. API NO.
15. ELEVATIONS (SHOW OF, KDB, AND WD)  
3887.1 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11/15/83 RU BOP & POH w/279 jts 2 7/8" tbgs. Perf w/1 spf 8407-8356'

11/17/83 Set pkr @ 8238'. Ru & load back side, acidize down tbgs w/4000 gal 20% SRA-100 w/120 1.1 Sp. Gr ball sealers. Flush w/100 bbls fresh water. Ru production wellhead equipment.

11/18/83 Hang well on production, good pump action.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Res. Engineer DATE December 21, 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ DATE MAY 8 1984

TITLE

DATE

Carlsbad

ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side

RECEIVED  
MAY 9 1984  
C.C.D.  
HOBBS OFFICE