

POSWELL, NEW MEXICO 88240

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Harvey E. Yates Company
3. ADDRESS OF OPERATOR
P. O. Box 1933, Roswell, New Mexico 88201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 1980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) Production Casing & Cement Report

5. LEASE
NM-036852

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Young Deep 3 Federal

8. FARM OR LEASE NAME

9. WELL NO.
3

10. FIELD OR WILDCAT NAME
North Young Bone Spring

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 3, T-18S, R-32E

12. COUNTY OR PARISH 13. STATE
Lea NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3887.1 GL

NOTE: Report results of multiple completion or zone change on Form 9-330.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/31/81 Day 53, Operation - RDRT, Depth - 9500' TD. Circ 3 1/2 hrs, Tagging plug 1/2 hr, LD DP 6 1/2 hrs, Ran csg 6 1/2 hrs, Cmt 1 hr, Set slips 1/2 hr. Rig released @ 1:30 a.m. 12/31/81. Ran 210 jts (8596.60') 5 1/2" 15.5# & 17# csg & set @ 8595'. CMTd w/190 sx Class "H" plus 1.25% CF-9, .1% WR-10, 2% Kcl & 1/4# Celloseal. Plug down @ 10:30 p.m. 12/30/81 w/1500 psi. Held OK. Csg breakdown:

38 jts	5 1/2"	17# LT&C J-55	1585.99'
136 jts	5 1/2"	15.5# LT&C J-55	5496.59'
36 jts	5 1/2"	17# LT&C J-55	1514.02'
210 jts			8596.60'

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

ROBERT A. CHAPMAN

TITLE

Engineer

DATE

January 7, 1982

JAN 11 1982

This space for Federal or State office use

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY.

TITLE

DATE

U.S. GEOLOGICAL SURVEY
POSWELL, NEW MEXICO