

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
The Superior Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 3901, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL, 1980' FEL, Sec. 23.
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐

☒ From Lea, Bone Spring to Wildcat - San Andres

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Recap of Recompletion in San Andres Zone

7-19-84 MI RU Bell Petroleum Services.

7-20-84 Set 5-1/2" 20# CIBP @ 9740'. Loaded hole w/210 bbls fresh water 2% KCL. Tested CIBP to 1000# PSI - O.K. Dumped 35' cmt on top of CIBP @ 9740' (TOC @ 9705'). Spotted 150' plug W 8260'. Used 16 sx Class H Cmt. Spotted 150' plug @ 6225'. Used 15 sx Class H Cmt. Reversed out w/38 bbls fresh water. SION.

7-21-84 Perfed San Andres 6036-6033'; 6030-6027'; 6020-5992' w/3-1/8" gun w/120° phasing. Perfed w/1 JSPS.

(Over)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED G.E. Tate G.E. Tate TITLE Division Opr. Supt. DATE 8-28-84

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE _____ DATE _____
CONDITIONS OF APPROVAL

AUG 31 1984

NEW MEXICO See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-140

7-22-81 Swabbed.

7-23-81 SI for Sunday

7-24-81 Acidized San Andres perfs w/4000 gals 15% HCL acid + additives w/1000 SCF/bbls N2. Swabbed.

7-25-81 Swabbed.

7-26-81 Swabbed

7-27-81 Set 5-1/2" 20# RPB @ 5960', tested to 1000# - O.K.
Perf'd San Andres 5860', 5882', 5885', 5892', w/1 USPF using 3-1/8" gun w/120° phasing. Swabbed.

7-28-81 Swabbed

7-29-81 Acidized San Andres (5860-5892') w/3000 gals HCL 15% acid + additives. Swabbed.

7-30-81 Swabbed.

7-31-81 RIH, latched on to RBP, POOH w/ same.

8-01-81 MI RU BJ-Hughes, frac'd San Andres perfs (5860-6036') w/30,000 gals gelled cross-link KCL frac fluid w/68,000# 20-40 mesh sand.

8-02-81 Opened well to test tanks.

8-03-81 Swabbed.

8-04-81 RIH w/production equipment. Started testing well.