

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

IL CONSERVATION DIVISIO.

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.L.	
LAND OFFICE	
OPERATION	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LG-3173

SUNDRIY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. Name of Operator
Union Oil Company of California

2. Address of Operator
P. O. Box 671 Midland, Texas 79702

3. Location of well
UNIT LETTER **F**, **1880** FEET FROM THE **North** LINE AND **1980** FEET FROM
THE **West** LINE, SECTION **33** TOWNSHIP **19-S** RANGE **33-E** N.M.P.M.

7. Unit Agreement Name
8. Farm or Lease Name
Maduro Unit State

9. Well No.
3

10. Field and Pool, or Wildcat
Undesignated Morrow

12. County
Lea

15. Elevation (Show whether DF, RT, GR, etc.)
3,539' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-17-82 - MI RU csg pulling unit. Ran 2-3/8" OD tbg OE'd to 8,000'. Cir hole w/10.5# mud. POOH w/tbg prepare to pull 5-1/2" OD csg.
5-19-82 - Wkd csg free @ 6,700'. Cut 5-1/2" OD csg @ 6,700'.
5-20-82 - Pulled and laid down 6,700' 5-1/2" OD csg.
5-21-82 - Plug No. 1 - Ran tbg to 6,710' & spotted 50 sx Class "H" cmt 6,710'-6,590'.
Plug No. 2 - Spotted 75 sx cmt 5,450'-5,315'.
Plug No. 3 - Spotted 50 sx cmt 3,324'-3,224'. Unable to pull 9-5/8" OD csg.
Plug No. 4 - Ran tbg to 1,300' & spotted 45 sx cmt 1,300'-1,165'.
Plug No. 5 - Spot 10 sx cmt 15' to surface. Pump 10.5# mud between plugs.
Weld on 4" x 4" dry hole marker. Clean location. WELL PLUGGED AND ABANDONED
5-24-82.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W.S. Walton For JAH
J. R. Hughes

TITLE Dist. Drilling Supt.

DATE 5-25-82

APPROVED BY A. G. Spattermead

TITLE OIL & GAS INSPECTOR

DATE AUG 18 1982

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY 26 1982

S.C.B.
HOLERS OFFICE