

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501Form C-103  
Revised 10-7

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER - PXA	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name Record
3. Address of Operator P. O. Box 68, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of well UNIT LETTER F 1980 FEET FROM THE North LINE AND 2180 FEET FROM THE West LINE, SECTION 25 TOWNSHIP 19-S RANGE 35-E N.M.P.M.	10. Field and Pool, or wildcat Und. Wolfcamp
15. Elevation (Show whether DF, RT, GR, etc.) 3676.6 GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐PLUG AND ABANDON ☐  
CHANGE PLANS ☐OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐ALTERING CASING  
PLUG AND ABANDONMENTOTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Moved in service unit 3-10-83. Pulled rods and pump. Circulated hole with 350 barrels brine water and recovered 80 barrels of oil. Unseated tubing anchor and pulled tubing. Ran in hole with CIBP and set at 8350'. Displace hole with gelled brine water. Spotted 35' of cement on CIBP. Displaced hole with gelled brine water. Spotted 25 sack cement plug at 5250'. Ran freepoint survey. Freepoint at 4340'. Cut casing at 4305'. Pulled 7-5/8" casing. Loaded hole. Spotted 100 sack cement plug at 4350'. Spotted 225 sack cement plug from 550' to surface. Welded on cap and erected PXA marker.

0+5-NMOCD,H 1-HOU 1-F. J. Nash, HOU 1-DMF

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mark FreemanTITLE Assist. Admin. AnalystDATE 3-25-83ORIGINAL SIGNED BY HARRY SEXTON  
DISTRICT 1 SUPERVISOR

APPROVED BY

TITLE

DATE

MAY 15 1985

CONDITIONS OF APPROVAL, IF ANY: