

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
Aminoil USA, Inc.

3. ADDRESS OF OPERATOR
P. O. Box 10525, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FWL & 2310' FSL of Section
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
NM - 073240

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal 30

9. WELL NO.
2

10. FIELD OR WILDCAT NAME
Gem Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 30, T-19-S, R-33-E

12. COUNTY OR PARISH
Lea

13. STATE
New Mexico

14. API NO.
NM -073240

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3589.2 GR


REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

(other) Activity for 1/9/82 to 1/15/82



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/9/82 TD 5315', Installed 12" X 9-5/8" casing spool, NU BOP'S & Hydril, tested BOP'S to 5000# - ok, tested Hydril to 2500# - ok
1/10/82 TD 5315', Drilled out DV Tool @ 2910', tsted casing to 1500# - ok & Drilled out cement.
1/11/82 TD 5315', TIH w/ Pkr to squeeze casing seat (pmp trucks froze)
1/12/82 TD 5315', Squeezed casing seat w/200 sx class "H", W.O.C.
1/13/82 TD 5315', Tagged cement & Drilled to 5315', tested casing to 1200# Bled down, re-squeezed w/200 sx class "H", W.O.C.
1/14/82 TD 5315', W.O.C., tagged cement @ 5229' & began drilling out cement.
1/15/82 TD Drilling @ 5510', wt 8.9.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE District Operations Manager DATE January 15, 1982

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY: _____

FOR RECORD
ROSEL A. CHAPMAN
JAN 20 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side