

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

OIL & GAS
1. oil well ☐ gas well ☒ other ☐ **MINERALS MGMT. SERVICE**
ROSWELL, NEW MEXICO
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, New Mexico 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL X 1980' FWL, Sec. 7
AT TOP PROD. INTERVAL: (Unit F, SE/4, NW/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input checked="" type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)			

5. LEASE NM-40450
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Federal "CS" Com.
9. WELL NO. 1
10. FIELD OR WILDCAT NAME Wildcat Yates
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 7-18-32
12. COUNTY OR PARISH Lea 13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3786.3 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 10-12-82. Pumped 10 bbl brine water down hole. Pulled tubing and packer. Ran cast iron bridge plug and set at 7359' to abandon Bone Springs. Spotted cement from 7350'-7250'. Spotted mud from 7250'-4410'. Spotted 100' cement plug from 4410'-4310'. Perforate 2778'-2790' with 4 SPF and 90° phasing. Ran in hole with tailpipe, packer, and tubing. Packer set at 2504' and tailpipe set at 2570'. Ran swab and recovered 9 BLW. Acidized with 1,500 gal 15% NEFE HCL acid and additives. Flush with 1,000 gal brine water. Flowed apx. 24 BLW. Ran swab and recovered 60 BLW and 6 BBL new water. No show of oil or gas. Moved out service unit 10-18-82. Currently evaluating.

O+6-MMS,R 1-HOU 1-W. Stafford, HOU 1-CMH

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Parker M. Serring TITLE Ast. Adm. Analyst DATE 10-26-82

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

PETER W. CHESTER

NOV 15 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

(This space for Federal or State office use)

TITLE _____ DATE _____

*See Instructions on Reverse Side

RECEIVED

NOV 17 1982

CCC
HOLDS OFFICE