

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL X 1980' FEL, Sec. 14
AT TOP PROD. INTERVAL: (Unit B, NW/4NE/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☒
☐
☐
☐
☐
☐

5. LEASE

NM-40452

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "BY"

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat Wolfcamp

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

14-18-32

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3825 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in wireline unit and ran bottom hole pressure bomb to 10,602'. Bottom hole pressure 3301 psi. Pull up bottom hole bomb and move out wireline unit. Moved in service unit 11-24-82. Acidized Wolfcamp interval with 5,000 gal 40# gelled brine pad and 5,000 gal 20% NEFE HCL acid. Flushed with 5,000 gal brine water. Maximum pressure 6900 psi and minimum pressure 6,000 psi. Opened well up and recovered 95 BLW. Swabbed well 51 hrs. and recovered 8 BO, 257 BLW, 5'-10' flare after each run. Flare decreased to 3 -5' in 5 minutes. Currently swab and flow testing well.

0+6-MMS, R 1-HOU 1-W. Stafford, HOU 1-CMH

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Charles M. Verrey

TITLE

Asst. Adm. Analyst

DATE

12-3-82

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAN 11 1983

MINERALS MANAGEMENT SERVICE
ROSWell, NEW MEXICO