

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be rounded off by this. In the case of directionally drilled wells, true vertical depth shall also be reported for multiple completions, item 27 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where triplicates are required. See Rule 1135.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn 11,556	T. Kitland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka 11,685	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 5397	T. Simpson	T. Gallup	T. Ignacio Quito
T. Glorieta 6892	T. McKee	T. Base Greenhorn	T. Granite
T. Permian 4. Clearfork	T. Ellenburger	T. Dakota	T.
T. Permian 8560	T. Gr. Wash	T. Morrison	T.
T. Permian 3rd Bone Springs	T. Granite	T. Todilto	T.
T. Permian 9595	T. Delaware Sand	T. Entrada	T.
T. Abo 9904	T. Bone Springs	T. Wingate	T.
T. Wolfcamp 10,020	T.	T. Chino	T.
T. Penn.	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.	
No. 2, from.....to.....feet.	
No. 3, from.....to.....feet.	
No. 4, from.....to.....feet.	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
5397	6892	1495	San Andres Dol. & LM.				
6892	7080	188	Glorieta Dolomite Sand				
9904	10,020	116	ABO Dolomite				
11,556	11,685	129	Strawn Limestone				
10,020	11,556	1536	Wolf Camp Lime & shale				

RECEIVED
DEC 6 1982
O.C.D.
HOBBS OFFICE