

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
SALE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2068

SANTA FE, NEW MEXICO 87501

Form C-113
Revised 10-1-73

56. Indicate Type of Lease	
State ☒	Free ☐
57. State Oil & Gas Lease No.	
--	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPERFORATE OR PLUG SALES IN A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-112) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		7. Unit Agreement Name	
2. Name of Operator		8. Name of Lease	
Mid-America Petroleum, Inc.		New Mexico State	
3. Address of Operator		9. Well No.	
P. O. Box 2515, Midland, Texas 79702		3	
4. Location of Well		10. Field and Pool, or Wildcat	
UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>north</u> LINE AND <u>1650</u> FEET FROM		East La Rica Morrow	
THE <u>east</u> LINE, SECTION <u>2</u> TOWNSHIP <u>19S</u> RANGE <u>34E</u> NE 1/4			
11. Elevation (Show whether DF, RT, GR, etc.)		12. County	
3973' GR		Lea	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) Drilled out from under surface casing to 1602'. Surveys showed deviation of 5° at 999' and 8-1/4° at 1602'.
- 2) Cemented hole w/770 sacks Class C containing 1# salt/sx from 1602' back into surface pipe at 540'.
- 3) Drilled new hole tagging top of cement at 510', (30' inside surface casing).
- 4) Drilled 12-1/4" hole to 4400'.
- 5) Set 105 jts. (4400') 8-5/8" J-55 8RD (2188') 32# and (2212') 24# casing at 4400' and cemented in two stages w/DV tool set at 2721'.
- 6) Cemented first stage w/525 sx. Class C. Bumped plug w/1500 psi. Float held okay. Dropped bomb and opened DV tool. Circulated through DV tool 2 hrs.
- 7) Cemented second stage w/575 sacks 65/35 Class C Lite Poz containing 6% D20 gel and 5# salt/sx. Plugged down at 11:00 p.m. 7-10-82.
- 8) WOC 18 hrs. Cut off casing.
- 9) NU BOP and tested BOP and casing to 3500# for 30 min., held okay. Picked up 7-7/8" bit and drilled ahead.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ed Robinson

TITLE Drilling Engineer

DATE July 12, 1982

ORIGINAL SIGNED BY

JERRY JOXSON

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUL 14 1982