

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

0. LEASE DESIGNATION AND SERIAL NO.

NM-67986

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Xion Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

No. 1 Young Undesignated Bone Spring

11. SEC., T., R., M., OR S.E. AND SURVEY OR AREA

Sec 18-T18S-R32E

14. PERMIT NO.

30-025-27846

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3751.4'

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PCLL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud, run csq & cmtg

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1/18/88 Rigged Up Reverse Unit & Pulling Unit & began drilling surface plug.
1/19-27/88 Cleaned out hole to total depth of 8763'. Ran 226 joints (8573') of 4 1/2" 15.1# casing with float shoe & float collar. Set & cemented @ 8570' w/600 sks 50/50 POZ Class H w/5# salt, .3 of 1% Halad 22A w/750 gal. mud flush ahead of cmt. Plug down @ 4:30 p.m. 1/27/88. Press to 3000#, held OK. WOC.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Jackie Midkiff/Landwoman

DATE 2/4/88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side