

N. M. OIL CONS. COMMISSION
P. O. BOX 1980
HOBBS, NEW MEXICO 88240

Form Approved.
Budget Bureau No. 42-61113

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen on a well back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
THE SUPERIOR OIL COMPANY

3. ADDRESS OF OPERATOR
P. O. Box 3901, Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL & 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☒ Weekly Drilling Report & Casing Detail

SUBSEQUENT REPORT OF:

5. LEASE
NM-086

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Government "E"

9. WELL NO.
7

10. FIELD OR WILDCAT NAME
Pearl (Bone Spring) Field

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 25, T19S, R34E

12. COUNTY OR PARISH, 13. STATE
Lea New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3773.5 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-25-82 Svy @ 9774=1 1/4°. Drig to 9935'.

9-26-82 Svy @ 10,083=3/4°. Drig to 10,362'.

9-27-82 Svy @ 10,362=3/4°. Circ. & cond. hole for logs.

9-28-82 Logging.

9-29-82 RU' csg crew. Running 5 1/2" csg - 140 jts.

9-30-82 Run 263 jts 5 1/2" csg. Cementing. 1st stage - 500 gals preflush, 300 sks HLW + additives. 2nd stage - 710 sks 50/50 POZ Cl. "H" + additives. FINAL REPORT.

Subsurface Safety Valve: Manu. and Type

Set @ _____ ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

ACCEPTED FOR RECORD
G. E. Tate

TITLE Prod. Supt.

DATE 10-5-82

APPROVED BY
CONDITIONS OF

(ORIG. SCD.) DAVID R. GLASS

APPROVED AND
OCT 8 1982

TITLE

DATE

U.S. GEOLOGICAL SURVEY
POSWELL, NEW MEXICO

*See Instructions on Reverse Side