

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1995

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.
NM 9218

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation
NMNM 91005X

8. Well Name and No.

OPOASU #6

9. API Well No.

30-025-27909

10. Field and Pool, or Exploration Area
Querecho Plains Queens
Associated Sand Unit

11. County or Parish, State

Lea Co., NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Mewbourne Oil Company

3. Address and Telephone No.

P.O. Box 5270, Hobbs, NM 88241 (505) 393-5905

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FSL & 330' FEL of Sec. 22, T18S, R32E

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☒ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/06/96 MIRU Well Service Rig. LD rods and pump. POOH w/tbg.
11/07/96 RIH w/tbg and pkr. Set pkr at 3784'. Acidized perf's w/3000 gal. 15% NE-FE. Rls. pkr. Set btm pkr 4040.7 and top pkr at 3810'. Pumped 45 bbls pkr fluid down annulus. Annulus would not load. Rls on-off tool on btm pkr and POOH w/top pkr and tbg.
11/08/96 RIH w/top pkr and tbg. Set top pkr. Loaded annulus and pressured up to 300 psi and pkr would not hold. POOH w/both pkr's. RIH w/tbg and pkr's. Bottom pkr set at 4011.6'. Side pocked mandrel set at 3912.05'. Top pkr set at 3781'. Perf's Queen and Penrose Sands (3881'-3916', 4090'-4151'). Loaded and tested annulus to 500 psi. Held OK.
11/13/96 Performed MIT on csg. Chart given to OCD representative. Put well on injection.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Petroleum Engineer

Date

11/22/96

(This space for Federal or State Office use)

BY

Title

Date

JAN 09 1997

Approved by

Conditions of approval, if any

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

*See instruction on Reverse Side

JC BN

MP
ds

