

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate
(Other instructions on
reverse side)

N. M. OIL CONS. COMMISSION

O. BOX 1330

Form Approved.
Budget Bureau No. 42-R1424.
OBBS-NEW MEXICO 88270

NM 9218

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR Mewbourne Oil Company		7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR P. O. Box 7698, Tyler, Texas 75711		8. FARM OR LEASE NAME Federal "F"
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FSL & 330' FEL		9. WELL NO. 2
14. PERMIT NO.		10. FIELD AND POOL, OR WILDCAT Querecho Plains - Queen Associated Pool
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3761.3' GL		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 22-18S-32E
		12. COUNTY OR PARISH Lea
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Setting of Intermediate String X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 31 joints (1182') 8-5/8" 24# & 32# J-55 casing set at 1194' - Cemented with 300 sacks Lite + 1/4# celloseal + 2% KCL and 200 sacks Class "C" + 2% CaCl.
Pressure tested casing to 600 psi - circulated 50 sacks - Plug down @ 9:45 P.M.
11/12/82.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Exploration Secretary

DATE 11/18/82

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

(ORIG. SGD.) DAVID R. GLASS

DATE

CONDITIONS OF APPROVAL

NOV 24 1982

U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO *See Instructions on Reverse Side

RECEIVED

NOV 29 1982

O.C.D.
HOBBS OFFICE