

UNITED STATES N. M. DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY HOBBS, NEW MEXICO

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 8675

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

|   |  |  |                   |
|---|--|--|-------------------|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>  |  | 7. UNIT AGREEMENT NAME   |                   |
| 2. NAME OF OPERATOR<br>Mewbourne Oil Company  |  | 8. FARM OR LEASE NAME<br>Federal "H"                                   |                   |
| 3. ADDRESS OF OPERATOR<br>P. O. Box 7698, Tyler, Texas 75711  |  | 9. WELL NO.<br>1   |                   |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)<br>At surface<br><br>660' FSL and 660' FEL |  | 10. FIELD AND POOL OR WILDCAT<br>Querecho Plains-Queen Associated Pool |                   |
|   |  | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA<br>22-18S-32E         |                   |
| 14. PERMIT NO.  | 15. ELEVATIONS (Show whether DF, RT, GR, etc.)<br>3759.1' GL | 12. COUNTY OR PARISH<br>Lea  | 13. STATE<br>N.M. |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
(Other) ☐

PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
ABANDON\* ☐  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐  
FRACTURE TREATMENT ☐  
SHOOTING OR ACIDIZING ☐  
(Other) ☐

REPAIRING WELL ☐  
ALTERING CASING ☐  
ABANDONMENT\* ☐

(Other) Setting of Production String ☒  
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Ran 108 jts 4-1/2" 11.6# J-55 8rd casing. Set at 4290' GL (4300' KB). Halliburton cemented with 600 sacks HLC w/15# salt + 1/4# flocele and 300 sacks Class "C" w/6# salt + .3% Halad 4. Displaced w/250 gal. MSA + 60 bbls KCL water. Plug down @ 5:15 AM 9/10/82. Circulated 60 sacks cement.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Exploration Secretary

DATE 9/10/82

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY  
CONDITIONS OF

OCT 8 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

RECEIVED

SEP

OIL & GAS  
MINERALS MGMT. SERVICE  
ROSWELL, NEW MEXICO