

This form is to be filled with the original data for the completion of any newly drilled or deepened well. It should be completed by the person in charge of the well and the name of all special tests conducted, including drill stem tests. All depths reported shall be rounded down. In the case of dipperingly drilled wells, true vertical depths shall also be reported. For multiple completions, the thickness of each zone shall be reported for each zone. The form is to be filled to quadruplicate except on state land, where six copies are required. See rule 1-1-15.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn 11,418'	T. Kitland Fruitland	T. Penn. "C"
B. Salt	T. Atoka 11,684'	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 5,280'	T. Simpson	T. Gallup	T. Ignacio Quartz
T. Guejito 7,008'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Iditarby	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilte	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo 9,818'	T. Bone Springs 9,466'	T. Wingate	T.
T. Wolfcamp 9,958'	T.	T. Chinle	T.
T. Penn.	T.	T. Pennian	T.
T. Cisco (Group C)	T.	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 11,477' to 11,481'	No. 4, from
No. 2, from 11,499' to 11,501'	No. 5, from
No. 3, from 11,515' to 11,539'	No. 6, from

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet
No. 4, from	to	feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	2,240	2,240	Red Beds				
2,240	3,250	1,010	Anhydrite & Shale				
3,250	4,710	1,460	Salt & Anhydrite				
4,710	5,300	590	Anhydrite & Dolomite				
5,300	6,645	1,345	Dolomite				
6,645	7,080	435	Dolomite & Limestone				
7,080	8,000	920	Dolomite				
8,000	8,480	480	Dolomite & Shale				
8,480	9,800	1,320	Dolomite & Sand & Shale				
9,800	10,100	300	Dolomite & Limestone				
10,100	11,425	1,325	Limestone & Shale				
11,425	11,670	245	Limestone				
11,670	11,742	72	Sand & Shale				

RECEIVED
MAY 3 1983
MODES OFFICE