

EQUIPMENT & HOLE DATA

FORMATION TESTED: BONE SPRING
NET PAY (ft): 29.0
GROSS TESTED FOOTAGE: 65.0
ALL DEPTHS MEASURED FROM: KELLY SHUMLING
CASING PERFS. (ft): 0
HOLE OR CASING SIZE (in): 7.875
ELEVATION (ft): 5840
TOTAL DEPTH (ft): 9315.0
PACKER DEPTH(S) (ft): 9245, 9251
FINAL SURFACE CHOKE (in): 0
BOTTOM HOLE CHOKE (in): 0.750
MUD WEIGHT (lb/gal): 8.40
MUD VISCOSITY (sec): 36
ESTIMATED HOLE TEMP. (°F): 130 @ 9311.0 ft
ACTUAL HOLE TEMP. (°F): 130 @ 9311.0 ft

TICKET NUMBER: 43714800

DATE: 2-28-03 TEST NO: 1

TYPE DST: OPEN HOLE

HALLIBURTON CAMP: ARTESIA

TESTER: MR. R. THOMAS

WITNESS: MR. C. BELLAH
MR. L. ARNOLD

DRILLING CONTRACTOR: W E K RIG #2

FLUID PROPERTIES FOR RECOVERED MUD & WATER

SOURCE	RESISTIVITY	CHLORIDES
	°F	ppm
	°F	ppm
	°F	ppm
	°F	ppm
	°F	ppm
	°F	ppm

SAMPLER DATA

Pstlg AT SURFACE: 50
cu.ft. OF GAS: 0.00
cc OF OIL: 0
cc OF WATER: 0
cc OF MUD: 0
TOTAL LIQUID cc: 850

HYDROCARBON PROPERTIES

OIL GRAVITY (°API): 0 °F
GAS/OIL RATIO (cu.ft. per bbl): 0
GAS GRAVITY: 0

CUSHION DATA

TYPE AMOUNT WEIGHT

RECOVERED:

40 FEET OF SLIGHT GAS CUT DRILLING FLUID

MEASURED FROM
TESTER VALVE

REMARKS:

DRILL PIPE AND DRILL COLLAR LENGTHS WERE NOT REPORTED.