

N.M. Oil Cons. Division
P.O. Box 1980
Hobbs, NM 88241
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

SEP 9 1 37 PM '96

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

Lease Designation and Serial No.

NM 0554858

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to ~~BUREAU OF LAND MGMT~~ reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

HOBBS, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Lynx Petroleum Consultants, Inc.

3. Address and Telephone No

P.O. Box 1979, Hobbs, NM 88241 (505) 392-6950

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & FEL

Section 9, T-19S, R-35E

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Government "9" #1

9. API Well No.

30-025-28157

10. Field and Pool, or Exploratory Area

Scharb Bone Springs

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

August 23, 1996

1. Set C.I.B.P. at 9450'.
2. Circulated hole with Brine Gelled Mud.
3. Spotted 10 sxs cement on top of C.I.B.P. (9450-9390').
4. Spotted 25 sxs cement 7000-6851'.
5. Spotted 25 sxs cement 4170-4021'.
6. Spotted 25 sxs cement 1675-1526'.
7. Spotted 30 sxs cement 485-324'. Tagged plug.
8. Spotted 10 sxs cement at surface.
9. Installed dry-hole marker.
10. Cut off anchors.
11. Will begin removal of equipment followed by location clean up.

14. I hereby certify that the foregoing is true and correct

Signed

Alexis C. Swoboda

Title President

Date 9/3/96

(This space for Federal or State office use)

Approved: (ORIG. SGD.) ALEXIS C. SWOBODA
Conditions of approval, if any.

Title PETROLEUM ENGINEER

Date 10/10/96