INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or desprined well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, liems 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

	Southeast	tern New Mexico	Northwestern New Mexico			
Т.	Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"		
т.	Salt	. T. Strawn	T. Kirtland-Fruitland	_ T. Penn. "C"		
B.	Salt	T. Atoka	T. Pictured Cliffs	_ T. Penn. "D"		
Т.	Yates	. T. Miss	T. Cliff House	T. Leadville		
т.	7 Rivers	T. Devonian	T. Menefee	T. Madison		
т.	Queen	T. Silurian	T. Point Lookout	_ T. Elbert		
Т.	Grayburg	T. Montoya	T. Mancos	_ T. McCracken		
Т.	San Andres 5324	T. Simpson	T. Gallup	_ T. Ignacio Qtzte		
Т.	Glorieta	. T. McKee	Base Greenhorn	T. Granite		
т.	Paddock	T. Ellenburger	T. Dakota	- T		
Т.	Blinebry	T. Gr. Wash	. T. Morrison	_ T		
т.	Tubb	. T. Granite	T. Todilto	T		
т.	Drinkard	T. Delaware Sand	T. Entrada	_ T		
Т.	Abo	T. Bone Springs 9238	- T. Wingate	- T		
				T		
				T		
т	Cisco (Bough C)	T	T. Penn "A"	T		
			SANDS OR ZONES			
No.	1, from 10,510'	to10_539'	No. 4, from	to		
No.	2, from	to	No. 5, from			
No.	\$, from	to	No. 6, from	to		

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None	to	feet.	
No. 2, from	to	ícet.	
No. 3, from	to	f cet.	
No. 4, from	_to	fcet.	

FORMATION RECORD (Attach additional sheets if necessary)

From	T٥	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
tart Log	7000			10,390	10,53	5'	SH/LS/CHT
7000 ⁻	7100		DOL/SD	10,535	10,80		LS/SH/SD/CHT
7100'	7480'		SD		,		
7480 '	7680		SD/SH				
7680'	7715		SH/SD/LS				
7715'	8420		LS/some shale		:		
8420'	9160		SH/LS/CHT				
9160'	9280		LS/SH				
9280'	9490		LS/SH/DOL/SD				
9490'	10,015		LS/SH/SD				
10,015'	10,390		SH/LS/some SD				
							: